


Datenblatt für Artikel: DSZ458010-

DSZ Datakast 19" demonteerbaar 45HE

HxBxD 2105x800x1000mm

Datakast met geschroefd frame



SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 45U
- Width: 800mm
- Depth: 1.000mm
- Demountable Parts:
 - Front Part: 105mm
 - Rear Part: 105 mm
- Main Part welded:
 - 390mm at 600 deep enclosure
 - 590mm at 800 deep enclosure
 - 690mm at 900 deep enclosure
 - 790mm at 1.000 deep enclosure
 - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
 - 15 – 22U: 300 kg
 - 27 – 47 U: 400kg

- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 43mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 45mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D600 – 494mm
 - W600 x D800 – 694mm
 - W600 x D900 – 794mm
 - W600 x D1000 – 894mm
 - W600 x D1200 – 1.094mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.

- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Technische Daten

Breedte (mm)	800,00
Hoogte (mm)	2.105,00
Diepte (mm)	1.000,00
Nettogewicht (kg)	116,60
Omgevingstemperatuur min. (°C)	0
Omgevingstemperatuur max. (°C)	40
Hoogte eenheden	45HE 2105mm
Kleur	RAL 7035/ RAL 5005 Grijs/ blauw

Artikeltabelle

BEZEICHNUNG	BEST.NR.
DSZ Datakast 19" demonteerbaar 45HE HxBxD 2105x800x1000mm	DSZ458010
Datakast met geschroefd frame	
Optionele toebehoren	
Profielhalfcilinder 40mm 333/ 5333 1 sleutel en schroef M5	DV900333S
Schroef voor plaatsing inbegrepen in de levering	
Paneel borstelinvloer montage in dak 2HE RAL7035 grijs	DBK24800
DS Plaat 19" 2 ventilatoren en thermostaat 4HE RAL7035 grijs	DLT44802-A
Voor kasten DS, DSS en DSZ	
DS Sokkel dieptedelen 2stk. D=1000mm RAL7035	DSOT1210
DS Sokkelplaat breedte geperforeerd filter B=800mm RAL7035	DSOF1283
Standschrank, RAL7035	
Paneel 19" 5 ringen metaal 80x40mm 1HE RAL7035 grijs	DBC14805
Paneel 19" 5 ringen kunststof 40x83mm 1HE RAL7035 grijs	DBK14805
Legbord 19" vast D=450mm <80kg 1HE RAL7035 grijs	DFS14845-C
Stopcontactenbalk 19" 9x RANDAARDE 1HE kabel 3m	IU070114-3
STOPCONTACTEN MET RANDAARDE ZIJN NIET TOEGELATEN IN BELGIE	
Stopcontactenbalk 19" 7x RANDAARDE OSA 1,25HE PVC	IU070113
STOPCONTACTEN MET RANDAARDE ZIJN NIET TOEGELATEN IN BELGIE	

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
Stopcontactenbalk 19" 9x RANDAARDE 1 HE schakelaar STOPCONTACTEN MET RANDAARDE ZIJN NIET TOEGELATEN IN BELGIE	Q7070114-A
Stopcontactenbalk 19" 7x RANDAARDE 1 HE OSA STOPCONTACTEN MET RANDAARDE ZIJN NIET TOEGELATEN IN BELGIE	Q7070113-A
Bevestigingset 19" M6 50x moer/ schroef/ rondel	DSSRA050
S-Rack Montageplaat 19" 14HE geperforeerd Bevestigingsmateriaal inbegrepen in de levering	DMP1914
LED datakastverlichting magnetisch, 230VAC, Deurschakelaar automatisch in werking zodra de deur wordt geopend, externe voedingseenheid	DTLIGHT01
Switch 24xRJ45 10/100/1000, Silent, w/o fan, internal PSU Metal-Chassis, 19"	QLGSW2457
TOOLLESS LINE Patchpaneel 19" 24MOD (SFA/B) 1 HE RAL7035	HSER0240GS