

Datenblatt für Artikel: ESL820984-

Bollard light ALVA 940/ 170 OP 180° 600lm 840 MD IR DALI IP65

Diffuser: opal, graphite gray, protected from sea air, dirt-repellent thanks to powder coating with lotus effect, Integrated motion detector with DALI bus power supply, IR remote-controlled



Technische Daten

Hoogte (mm)	940,00
Netto diameter (mm)	170,00
Nettogewicht (kg)	7,83
Omgevingstemperatuur min. (°C)	-25
Omgevingstemperatuur max. (°C)	40
Type verlichting	Bollardverlichting
Bevestiging	Bodemmontage
Kleur	Grafiet
Stralingshoek (°)	283
Nominale werkspanning AC (V)	200-240
Lichtrendement (lm/W)	37
Vermogen (W)	17
Lichtkleur	Neutraalwit
Kleurtemperatuur (K)	4000
Kleurweergave-index (Ra)	80
MacAdam Kleurkwaliteit (sdcm)	1

Technische Daten - Fortsetzung

Lichtstroom (lm)	630
Levensduur	70.000h (L80B50)
Regelen lichtintensiteit	DALI Ja
Beschermingsklasse	1
Beschermingsgraad	IP65
Slagvastheid	IK09
Lichtmiddel inbegrepen	Inbegrepen
ØxH (mm)	170x940

BEZEICHNUNG	BEST.NR.
Bollard light ALVA 940/170 OP 180° 600lm 840 MD IR DALI IP65	
Diffuser: opal, graphite gray, protected from sea air, dirt-repellent thanks to powder coating with lotus effect, Integrated motion detector with DALI bus power supply, IR remote-controlled	ESL820984