

Datenblatt für Artikel: HSELS043CP

FO Splicebox 19" 1 HE 4x pigtails SC 50/125µm OM3 klasse C

conform IEC 61753-1 RAL7035 uittrekbaar



Schrack Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 SC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technische Daten

Breedte (mm)	480,00
Hoogte (mm)	44,00
Diepte (mm)	242,00
Nettogewicht (kg)	2,53
Type vezels	50/125µm OM3 multimode
Kleur	RAL 7035
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 35
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Aantal glasvezels	4

Artikeltabelle

BEZEICHNUNG	BEST.NR.
FO Splicebox 19" 1HE 4x pigtails SC 50/125µm OM3 klasse C conform IEC 61753-1 RAL7035 uittrekbaar	HSELS043CP
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
Glasvezelreinigingsstift SC, ST, FC en E2000 Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HSELSZT002
OPM200 Glasvezeltester voor vermogensmeting	HSELSZT003
FO Patchkabel Duplex SC/SC 50/125µm OM3 LSOH-3 aqua 2m Aqua	HLP23CC02F
FO Patchkabel Duplex SC/SC 50/125µm OM3 LSOH-3 aqua 5m Aqua	HLP23CC05F
FO Patchkabel Duplex LC/SC 50/125µm OM3 LSOH-3 aqua 2m Aqua	HLP23LC02F

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
FO Patchkabel Duplex LC/SC 50/125µm OM3 LS0H-3 aqua 5m LS0H, aqua	HLP23LC05F
FO Patchkabel Duplex ST/SC 50/125µm OM3 LS0H-3 aqua 2m LS0H, aqua	HLP23TC02F
FO Patchkabel Duplex ST/SC 50/125µm OM3 LS0H-3 aqua 5m LS0H, aqua	HLP23TC05F