


Datenblatt für Artikel: HSELS089DR

FO Splicebox DIN-rail 8x pigtails SC/APC

9/125µm OS2

RAL7035, incl. Pigtails, incl. couplers, CLASSIC



Technische Daten

Breedte (mm)	126,00
Hoogte (mm)	35,20
Diepte (mm)	155,65
Nettogewicht (kg)	0,59
Type vezels	9/125µm OS2 singlemode/ G.652D
Kleur	RAL 7035
Insertion loss typical (dB)	≤0,2
Return loss typical (dB)	≥50
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Aantal glasvezels	8
Glasvezelaansluiting	SC/APC

Artikeltabelle

BEZEICHNUNG	BEST.NR.
FO Splicebox DIN-rail 8x pigtails SC/APC 9/125µm OS2 RAL7035, incl. Pigtails, incl. couplers, CLASSIC	HELS089DR
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
Glasvezelreinigingsstift SC, ST, FC en E2000 Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HELSZT002
OPM200 Glasvezeltester voor vermogensmeting	HELSZT003
FO Patchkabel Duplex SC/APC-SC/APC 9/125µm OS2 geel 2m Geel LS0H-3	HLP29DD02F
FO Patchkabel Duplex SC/APC-SC/APC 9/125µm OS2 geel 5m Geel LS0H-3	HLP29DD05F
FO Patchkabel Duplex LC/APC-SC/APC 9/125µm OS2 LS0H-3 2m LS0H, yellow	HLP29MD02F
FO Patchkabel Duplex LC/APC-SC/APC 9/125µm OS2 LS0H-3 5m LS0H, yellow	HLP29MD05F