


Datenblatt für Artikel: HSELS089MR

FO Splicebox DIN-rail 8x pigtails LC/APC

9/125µm OS2

RAL7035, incl. Pigtails, incl. couplers, CLASSIC



Technische Daten

Breedte (mm)	126,00
Hoogte (mm)	35,20
Diepte (mm)	155,65
Nettogewicht (kg)	0,59
Type vezels	9/125µm OS2 singlemode/ G.652D
Kleur	RAL 7035
Insertion loss typical (dB)	≤0,2
Return loss typical (dB)	≥50
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Aantal glasvezels	8
Glasvezelaansluiting	LC/APC

Artikeltabelle

BEZEICHNUNG	BEST.NR.
FO Splicebox DIN-rail 8x pigtails LC/APC 9/125µm OS2 RAL7035, incl. Pigtails, incl. couplers, CLASSIC	HELS089MR
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
Glasvezelreinigingsstift LC en MU Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HELSZT001
OPM200 Glasvezeltester voor vermogensmeting	HELSZT003
FO Patchkabel Duplex LC/APC-LC/APC 9/125µm OS2 geel 2m Geel LS0H-3	HLP29MM02F
FO Patchkabel Duplex LC/APC-LC/APC 9/125µm OS2 geel 5m Geel LS0H-3	HLP29MM05F
FO Patchkabel Duplex LC/APC-SC/APC 9/125µm OS2 LS0H-3 2m LS0H, yellow	HLP29MD02F
FO Patchkabel Duplex LC/APC-SC/APC 9/125µm OS2 LS0H-3 5m LS0H, yellow	HLP29MD05F