

Datenblatt für Artikel: HSELS123CP

# FO Splicebox 19" 1 HE 12x pigtails SC 50/125µm OM3 klasse C

conform IEC 61753-1 RAL7035 uittrekbaar



## SCHRACK-Info

### Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:  
for 12 SC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:  
Chassis: 1,0mm  
Sliding tray: 1,25mm  
Frontpanel: 1,4mm  
19" holder: 1,5mm

## SPLICE-CASSETTES

- For shrink splice protectors  
up to 12 fibres: 1 splice-cassette  
up to 24 fibers: 2 splice-cassettes

## STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

## Technische Daten

|                                |                        |
|--------------------------------|------------------------|
| Breedte (mm)                   | 480,00                 |
| Hoogte (mm)                    | 44,00                  |
| Diepte (mm)                    | 242,00                 |
| Nettogewicht (kg)              | 2,53                   |
| Type vezels                    | 50/125µm OM3 multimode |
| Kleur                          | RAL 7035               |
| Insertion loss typical (dB)    | < 0,2                  |
| Return loss typical (dB)       | > 35                   |
| Omgevingstemperatuur min. (°C) | -10                    |
| Omgevingstemperatuur max. (°C) | 70                     |
| Aantal glasvezels              | 12                     |

## Artikeltabelle

| BEZEICHNUNG                                                                                                           | BEST.NR.   |
|-----------------------------------------------------------------------------------------------------------------------|------------|
| FO Splicebox 19" 1HE 12x pigtails SC 50/125µm OM3 klasse C<br>conform IEC 61753-1 RAL7035 uittrekbaar                 | HSLS123CP  |
| <b>Optionele toebehoren</b>                                                                                           |            |
| FO Splice lasbescherming 60mm (verpakking 10stk.)                                                                     | HELSP00011 |
| FO Splice lasbescherming 45mm (verpakking 10stk.)                                                                     | HELSP00010 |
| Glasvezelreinigingsstift SC, ST, FC en E2000<br>Suitable for UPC and APC connectors. More than 1,000 cleaning cycles. | HSLSZT002  |
| OPM200 Glasvezeltester voor vermogensmeting                                                                           | HSLSZT003  |
| FO Patchkabel Duplex SC/SC 50/125µm OM3 LSOH-3 aqua 2m<br>Aqua                                                        | HLP23CC02F |
| FO Patchkabel Duplex SC/SC 50/125µm OM3 LSOH-3 aqua 5m<br>Aqua                                                        | HLP23CC05F |
| FO Patchkabel Duplex LC/SC 50/125µm OM3 LSOH-3 aqua 2m<br>Aqua                                                        | HLP23LC02F |

## Artikeltabelle

| BEZEICHNUNG                                                          | BEST.NR.   |
|----------------------------------------------------------------------|------------|
| <b>Optionele toebehoren</b>                                          |            |
| FO Patchkabel Duplex LC/SC 50/125µm OM3 LS0H-3 aqua 5m<br>LS0H, aqua | HLP23LC05F |
| FO Patchkabel Duplex ST/SC 50/125µm OM3 LS0H-3 aqua 2m<br>LS0H, aqua | HLP23TC02F |
| FO Patchkabel Duplex ST/SC 50/125µm OM3 LS0H-3 aqua 5m<br>LS0H, aqua | HLP23TC05F |