

Datenblatt für Artikel: HSELS124LP

FO Splicebox 19" 1 HE 12x pigtails LC 50/125µm OM4 klasse C

conform IEC 61753-1 RAL7035 uittrekbaar



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technische Daten

Breedte (mm)	480,00
Hoogte (mm)	44,00
Diepte (mm)	242,00
Nettogewicht (kg)	2,53
Type vezels	50/125µm OM4 multimode
Kleur	RAL 7035
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 35
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Aantal glasvezels	12

Artikeltabelle

BEZEICHNUNG	BEST.NR.
FO Splicebox 19" 1HE 12x pigtails LC 50/125µm OM4 klasse C conform IEC 61753-1 RAL7035 uittrekbaar	HSLS124LP
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
Glasvezelreinigingsstift LC en MU Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HSLSZT001
OPM200 Glasvezeltester voor vermogensmeting	HSLSZT003
FO Patchkabel Duplex LC/LC 50/125µm OM4 LS0H-3 violet 2m LS0H, heather violet	HLP24LL02F
FO Patchkabel Duplex LC/LC 50/125µm OM4 LS0H-3 violet 5m LS0H, heather violet	HLP24LL05F
FO Patchkabel Duplex LC/SC 50/125µm OM4 LS0H-3 violet 2m LS0H, heather violet	HLP24LC02F
FO Patchkabel Duplex LC/SC 50/125µm OM4 LS0H-3 violet 5m LS0H, heather violet	HLP24LC05F