


Datenblatt für Artikel: HSELS129LR

FO Splicebox DIN-rail 12x pigtails LC

9/125µm OS2

RAL7035, incl. Pigtails, incl. couplers, CLASSIC



Technische Daten

Breedte (mm)	126,00
Hoogte (mm)	35,20
Diepte (mm)	155,65
Nettogewicht (kg)	0,59
Type vezels	9/125µm OS2 singlemode/ G.652D
Kleur	RAL 7035
Insertion loss typical (dB)	≤0,2
Return loss typical (dB)	≥50
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Aantal glasvezels	12
Glasvezelaansluiting	LC

Maattekening: FO Splicebox DIN-rail 12x pigtails LC 9/125µm OS2



Artikeltabelle

BEZEICHNUNG	BEST.NR.
FO Splicebox DIN-rail 12x pigtails LC 9/125µm OS2	HSELS129LR
RAL7035, incl. Pigtails, incl. couplers, CLASSIC	
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
Glasvezelreinigingsstift LC en MU	HSELSZT001
Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	
OPM200 Glasvezeltester voor vermogensmeting	HSELSZT003
FO Patchkabel Duplex LC/LC 9/125µm OS2 LS0H-3 geel 2m	HLP29LL02F
LS0H, yellow	
FO Patchkabel Duplex LC/LC 9/125µm OS2 LS0H-3 geel 5m	HLP29LL05F
LS0H, yellow	

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
FO Patchkabel Duplex LC/SC 9/125µm OS2 LS0H-3 geel 2m LS0H, yellow	HLP29LC02F
FO Patchkabel Duplex LC/SC 9/125µm OS2 LS0H-3 geel 5m LS0H, yellow	HLP29LC05F
FO Patchkabel Duplex LC/FC 9/125µm OS2 LS0H-3 geel 2m LS0H, yellow	HLP29LF02F