

Datenblatt für Artikel: HSELS245CP

FO Splicebox 19" 1 HE 24x pigtails SC 50/125µm OM2 klasse C

conform IEC 61753-1 RAL7035 uittrekbaar



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 SC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technische Daten

Breedte (mm)	480,00
Hoogte (mm)	44,00
Diepte (mm)	242,00
Nettogewicht (kg)	2,53
Afwerking	RAL 7035
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 35
Type vezels	50/125µm OM2 multimode
Aantal glasvezels	24

Artikeltabelle

BEZEICHNUNG	BEST.NR.
FO Splicebox 19" 1HE 24x pigtails SC 50/125µm OM2 klasse C conform IEC 61753-1 RAL7035 uittrekbaar	HSELS245CP
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
FO Patchkabel Duplex SC/SC 50/125µm OM2 LSOH-3 oranje 2m	HLP25CC02F
FO Patchkabel Duplex SC/SC 50/125µm OM2 LSOH-3 oranje 5m	HLP25CC05F
FO Patchkabel Duplex LC/SC 50/125µm OM2 LSOH-3 oranje 2m	HLP25LC02F
FO Patchkabel Duplex LC/SC 50/125µm OM2 LSOH-3 oranje 5m	HLP25LC05F
FO Patchkabel Duplex ST/SC 50/125µm OM2 LSOH-3 oranje 2m	HLP25TC02F
FO Patchkabel Duplex ST/SC 50/125µm OM2 LSOH-3 oranje 5m	HLP25TC05F