


Datenblatt für Artikel: HSKP422HG1

Kabel S/FTP Cat7a 1250Mhz LSOH-3 B2ca-s1a,d1,a1 50% GS 1000m

Kabel HSEKP422HG op rol 1000m



SCHRACK-Info

Installationcables for generic, structured network cabling systems. Support all applications requiring Class D to Class F_A (e.g. 10GBase-T, 1000Base-T, 100Base-TX, ATM) as well as VoIP, 4PPoE.

Supports 25Gbase-T (ISO/IEC TR 11801-9905).

Due to the cable construction and the high braid coverage of 50%, the cable reaches the coupling attenuation (Type I) of ≥ 85 dB.

25GB

Technische Daten

Categorie	Cat.7 _a
Kabelafscherming	S/FTP
Uitvoering geleider	Massieve koperdraad AWG22/1 (0,64mm)
Kleurcodering geleiders	Paar 1: wit/ blauw Paar 2: wit/ oranje Paar 3: wit/ groen Paar 4: wit/ bruin
Aantal paren	4, alle samen getwist

Technische Daten - Fortsetzung

Isolatiemateriaal	Geschuimd polyethyleen
Dikte isolatie (mm)	1,54
Afscherming	Met afscherming
Afscherming paren	Aluminium gelamineerd polyester
Algemene afscherming	Massief vertind koperdraad
Afscherming (%)	50
Ripcord	Nylon
Kabelmantel	LS0H-3
Materiaal buitenisolatie	LS0H-3, FRNC conform: IEC 61034-1/2, EN 50268-1/2 IEC 60754-1/2, EN 50267-1/2 IEC 60332-3-24, EN 60332-3-24
Euroklasse volgens EN50575	B2ca
Rook ontwikkeling/ dichtheid	s1a
Brandende druppels	d1
Weerstand zuurinwerking/ corrosiviteit	a1
Kleur buitenmantel	Grijs
Brandbelasting (kJ/m)	700
Buitendiameter (mm)	8,1
Nominaal gewicht (kg/km)	65
Afwerking	Grijs
Temperatuursbereik - Werking (°C)	-30°C tot +60
Temperatuursbereik - Transport/ Opslag (°C)	-30°C tot +60
Temperatuursbereik - Installatie (°C)	0°C tot +50
Buigradius kabel - Statisch (Ø)	4
Buigradius kabel - Dynamisch (Ø)	8
Maximale treksterkte (N)	110
Nominale spanning	≤72VDC/ ≤50VAC
Maximum continue stroom per geleider (bij 25°C) (A)	1,5
Gelijkstroomweerstand bij 20°C (Ohm/100m)	≤9,5
Weerstandasymmetrie: per paar / tussen paren (%)	≤2 / ≤4
DC isolatieweerstand (MΩ*km)	≥ 5000
Diëlektrische sterkte geleider - geleider (2s) (kV DC)	2,5
Diëlektrische sterkte geleider - afscherming (2s) (kV DC)	2,5
Wederzijdse capaciteit (nF/km)	≤56
Capacitance unbalance pair to ground (pF/km)	≤1600
SKEW (ns/100m)	≤ 25
Nominale voortplantingssnelheid (NVP) (%)	73
Kabellengtes	Trommel 1000m
IEEE Conformiteit	PoE: IEEE 802.3bt Type 1, Type 2, Type 3, Type 4

ELECTRICAL CHARACTERISTICS AT 20°C ACCORDING TO IEC 61156-5

	Freq. (MHz)	Specification	Unit
NVP (Nominal velocity of propagation)	4 – 1000	0.73	c
Skew	4 – 1000	≤ 25	ns/100m
Propagation delay	4 – 1000	≤ 534 + 36/Vf	ns/100m
Attenuation	5 – 1000	≤ 1.8*Vf+0.005*f+0.25/Vf	dB
TCL, level 1 (Transverse conversion loss)	1 – 250	> 40 – 10*log (f)	dB
ELTCL (Equal level transverse conversion loss)	1 – 30	> 35 – 20*log (f)	dB
NEXT (Near end cross talk)	4 – 1000	≥ 106-15*log (f) (78 max.)	dB
PS NEXT (Power sum near end cross talk)	4 – 1000	≥ 103-15*log (f) (75 max.)	dB
ACR-N (Attenuation cross talk ratio)	4 – 1000	NEXT – Dämpfung	dB
PS ACR-N (Power sum attenuation cross talk ratio)	4 – 1000	PSNEXT – Dämpfung	dB
ACR-F (Equal level far end cross talk)	4 – 1000	≥ 95.3-20*log (f) (78 max.)	dB
PS ACR-F (Power sum equal level far end cross talk)	4 – 1000	≥ 92.3-20*log (f) (75 max.)	dB
PS ANEXT (Power sum alien near end cross talk)	4 – 1000	≥ 107.5-15*log (f) (67 min.)	dB
PS AACR-F (Power sum alien far end cross talk)	4 – 1000	≥ 92.3-20*log (f) (67 min.)	dB
Input impedance open / short (Zo/s)	4 – 1000	100	Ω
RL (Return loss)	4 ≤ f ≤ 10	≥ 20 + 5*log (f)	dB
	10 ≤ f ≤ 20	≥ 25	dB
	20 ≤ f ≤ 600	≥ 25-7*log (f/20) (17.3 min.)	dB
	600 ≤ f ≤ 1000	≥ 17.3-10*log (f/600)	dB
Coupling attenuation (type I)	30 – 100	≥ 85	dB
	100 – 1000	≥ 85-20*log (f/100)	dB
Transfer impedance (ZT, grade 1)	1	< 10	mΩ/m
	10	< 10	mΩ/m
	30	< 30	mΩ/m
	100	< 100	mΩ/m

REFERENCE STANDARD AT 20°C: IEC 61156-5

Frequency	1*	4	10	16	30	62,5	100	155	250	500	600	1000	1250*	MHz
Attenuation	2,1	3,7	5,8	7,3	10,3	14,6	18,5	23,2	29,7	42,8	47,1	61,9	69,9	dB/100m
NEXT	78	78	78	78	78	78	76	73,1	70	65,5	64,3	61	59,5	dB/100m
PS NEXT	75	75	75	75	75	75	73	70,1	67	62,5	61,3	58	56,5	dB/100m
ACR-N	75,9	74,3	72,2	70,7	67,7	63,4	57,5	49,9	40,3	22,7	17,2	-0,9	-10,4	dB/100m
PS ACR-N	72,9	71,3	69,2	67,7	64,7	60,4	54,5	46,9	37,3	19,7	14,2	-3,9	-13,4	dB/100m
ACR-F	78	78	75,3	71,2	65,4	59,4	55,3	51,5	47,3	41,3	39,7	35,3	33,4	dB/100m
PS ACR-F	75	75	72,3	68,2	62,4	56,4	52,3	48,5	44,3	38,3	36,7	32,3	30,4	dB/100m
RL	20	23	25	25	23,6	21,5	20,1	18,8	17,3	17,3	17,3	15,1	14,1	dB/100m

* Limits below 4 MHz and values at 1250 MHz are for information only.

TYPICAL VALUES AT 20°C

Frequency	1*	4	10	16	30	62,5	100	155	250	500	600	1000	1250*	MHz
Attenuation	1,8	3,3	5,3	6,7	9,3	13,4	17,1	20,9	27	39,4	43,3	57,7	65,4	dB/100m
NEXT	103	100	98	97	95	94	93	92	91	90	89	88	87	dB/100m
PS NEXT	100	97	95	94	92	91	90	89	88	87	86	85	84	dB/100m
ACR-N	101	97	93	91	85	81	76	71	64	51	46	30	21	dB/100m
PS ACR-N	98	94	90	88	82	78	73	68	61	48	43	27	18	dB/100m
ACR-F	95	94	93	91	90	87	85	82	71	65	60	50	45	dB/100m
PS ACR-F	92	91	90	88	87	84	82	79	68	62	57	47	42	dB/100m
RL	27	30	32	32	35	33	32	31	27	23	23	19	18	dB/100m

* Limits below 4 MHz and values at 1250 MHz are for information only.

Artikeltabelle

BEZEICHNUNG	NVP (%)	KUPFERGEWICHT (kg/km)	BEST.NR.
Kabel S/FTP Cat7a 1250Mhz LSOH-3 B2ca-s1a,d1,a1 50% GS 1000m	73	35	HSKP422HG1
Kabel HSEKP422HG op rol 1000m			
Optionele toebehoren			
S-JACK Keystone RJ45 STP Cat.6a 10GB 4PPoE 100W SFB 24stk.			HSEMRJ6GS2
Per doos van 24stk.			
S-JACK Keystone RJ45 STP Cat.6a 10GB 4PPoE 100W SFB 1stk.			HSEMRJ6GS1
Beschikbaar per stuk			
TOOLLESS LINE Keystone RJ45 afgeschermd Cat.6a 10GB (SFA)			HSEMRJ6GWA
TOOLLESS LINE Keystone RJ45 afgeschermd Cat.6a 10GB (SFB)			HSEMRJ6GBA
Schrack Form B			
Kabelaflroller <250kg breedte <52cm			HTOOL00006
Kabelbinder Velcro 16mm rol 4m blauw			Q7KB0416-B
Kabelbinder Velcro 16mm rol 4m rood			Q7KB0416-R
Kabelbinder Velcro 16mm rol 4m zwart			Q7KB0416-S
Kabelbinder Velcro 16mm rol 4m geel			Q7KB0416-Y
Kabelbinder Velcro 16mm rol 4m groen			Q7KB0416-U