

Jack RJ45 unshielded, Cat.5e (SFA)



SCHRACK-Info

TRANSMISSION PERFORMANCE

- Meet all requirements specified in connecting hardware requirement of ANSI/TIA-568-C.2, Category 5e

ELECTRICAL

- Electrical Insulation Resistance: 500MΩ min. 100VDC
- Dielectric Withstanding Voltage : 1000VDC or a.c. Peak Contact to Contact 60Hz for 1 minute

MECHANICAL

- Insertion / Extraction Life: 750 Cycles Minimum
- IDC Wire Gauge: 22 ~ 24 AWG

PHYSICAL

- Housing: High-Impact, Flame-Retardant Plastic, UL 94V-0
- Spring Wire: Phosphor Bronze Alloy Plated with 50μ-inch of Gold
- IDC: Phosphor Bronze Alloy with 100μ-inch 100% Sn Alloy



Technische Daten

Breedte (mm)	16,90
Hoogte (mm)	21,90

Technische Daten - Fortsetzung

Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	60

Artikeltabelle

BEZEICHNUNG	NVP (%)	KUPFERGEWICHT (kg/km)	BEST.NR.
Jack RJ45 unshielded, Cat.5e (SFA)			HVSMRJ5UWS
Optionele toebehoren			
Crimping Tool for HVSMRJ5UWS / HVSMRJ6UWS			HVSTOOL01S
Kabel U/UTP Cat.5e 4x2xAWG24/1 PVC Eca blauw 305m Deze kabel is enkel beschikbaar in dozen van 305m.	69	15	HSEKU424P1
Kabel U/UTP Cat.5e 4x2xAWG24/1 PVC Eca 305m grijs Deze kabel is enkel beschikbaar in dozen van 305m.	69	15	HSEKU424P0
Kabel U/UTP Cat.5e 4x2xAWG24/1 LSOH Eca 305m blauw Deze kabel is enkel beschikbaar in dozen van 305m.	69	15	HSEKU424H1
TOOLLESS LINE Patchpaneel 19" 24MOD (SFA/B) 1HE RAL7035			HSER0240GS
TOOLLESS LINE DIN-rail adapter RJ45 keystone SFA/SFB RAL7035			HSEH010GS
Inbouwraam schuin voor 1 keystone SFA/ SFB 80x80mm wit RAL9010			HSED01UW2S
Inbouwraam schuin voor 2 keystones SFA/ SFB 80x80mm wit RAL9010			HSED02UW2S