

Datenblatt für Artikel: IG009401--

Cable management enclosure Series J, dotted, 1 door, size 00

H=1100 W=471 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technische Daten

Breedte (mm)	471,00
Hoogte (mm)	1.100,00

Technische Daten - Fortsetzung

Diepte (mm)	320,00
Nettogewicht (kg)	22,57
EAN CODE	4029155649922
Stroomwarmteverliezen (W)	-217,71
Uitvoering	Polyester glasvezelversterkt kunststof
Product	Kabelverdeelkast KVS
Hoogte (mm)	1100
Breedte (mm)	440
Diepte (mm)	320
Aantal deuren	1
Aantal deuren	Enkele deur geribbeld
Sluitingen	Zwenkgreep met halve cilinder
Kleur	RAL 7035
Beschermingsgraad	IP44
Beschermingsklasse	II
Slagvastheid	IK10

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Cable management enclosure Series J, dotted, 1 door, size 00 H=1100 W=471 D=320mm, door opening angle 180°		IG009401
Optionele toebehoren		
Mountingplate for IG009401, H=985 W=375 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009441
plastic base frame sizes 00/S3 and 0/S4 600/400 plastic base frame serving as a foundation for plinth		IG790328
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 00/S3/310 (absorption mat)		IG793816
Plinth Polyester Series J size 00, RAL7035 H=902 W=450 D=310mm		IG009311
Adapter bar for KVS - IG009401, size 00 (PU= 2 pcs.) Pre-cut with M6 machine tap bit		IG009461

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Optionele toebehoren		
Modular chassis 1-21K, 7-rows, complete		IL148121-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009401 & IG009501		IG009421
H=288 W=429 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 00		
For IG009401 and IG009501, 4 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	3400	IG00903100
Copper busbar, 30x10mm for Size 00		
For IG009401 and IG009501, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1120	IG009P3100
Afdekking 100mm voor railsysteem 185mm		ISA05360
For mounting on insert nuts M12		
Halfcilinder draaiend H36000 3 sleutels		IL900381
Voor IU001225/ IU001903		