

Datenblatt für Artikel: IG009403--

Cable management enclosure Series J, dotted, 1 door, size 1

H=1100 W=800 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technische Daten

Breedte (mm)	800,00
Hoogte (mm)	1.100,00

Technische Daten - Fortsetzung

Diepte (mm)	320,00
Nettogewicht (kg)	29,86
EAN CODE	4029155575313
Stroomwarmteverliezen (W)	-315,56
Uitvoering	Polyester glasvezelversterkt kunststof
Product	Kabelverdeelkast KVS
Hoogte (mm)	1100
Breedte (mm)	785
Diepte (mm)	320
Aantal deuren	1
Aantal deuren	Enkele deur geribbeld
Sluitingen	Zwenkgreep met halve cilinder
Kleur	RAL 7035
Beschermingsgraad	IP44
Beschermingsklasse	II
Slagvastheid	IK10

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Cable management enclosure Series J, dotted, 1 door, size 1 H=1100 W=800 D=320mm, door opening angle 180°		IG009403
Optionele toebehoren		
Mountingplate for IG009303, H=985 W=680 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009443
plastic base frame sizes 1/S5 800/400		IG790329
plastic base frame serving as a foundation for plinth		
base filler - hydrophobic		IG790333
100 liter bag, water-repellent - hydrophobic		
base filler expanded clay 4-8mm round 50L		IG790570
water-absorbing - expanded clay, 50 liter bag		
foam insert size 1/S5/310 (absorption mat)		IG793819
Plinth Polyester Series J size 1, RAL7035 H=902 W=780 D=310mm		IG009313
Adapter bar for KVS - IG009403, size 1 (PU= 2 pcs.) Pre-cut with M6 machine tap bit		IG009463

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Optionele toebehoren		
Modular chassis 3-21K, 7-rows, complete		IL148321-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009403 & IG009503		IG009423
H=288 W=758 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 1		
For IG009403 and IG009503, 7 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	6520	IG0090311
Copper busbar, 30x10mm for Size 1		
For IG009403 and IG009503, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1980	IG009P311
Copper busbar, 40x10mm for Size 1		
For IG009403 and IG009503, 7 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	8840	IG0090411
Afdekking 100mm voor railsysteem 185mm		ISA05360
For mounting on insert nuts M12		
Halfcilinder draaiend H36000 3 sleutels		IL900381
Voor IU001225/ IU001903		