

Datenblatt für Artikel: IG009405--

Cable management enclosure Series J, dotted, 2 doors, size 2

H=1100 W=1130 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technische Daten

Breedte (mm)	1.130,00
Hoogte (mm)	1.100,00

Technische Daten - Fortsetzung

Diepte (mm)	320,00
Nettogewicht (kg)	42,15
EAN CODE	4029155605294
Stroomwarmteverliezen (W)	-413,71
Uitvoering	Polyester glasvezelversterkt kunststof
Product	Kabelverdeelkast KVS
Hoogte (mm)	1100
Breedte (mm)	1115
Diepte (mm)	320
Aantal deuren	2
Aantal deuren	Dubbele deur geribbeld
Sluitingen	Zwenkgreep met halve cilinder
Kleur	RAL 7035
Beschermingsgraad	IP44
Beschermingsklasse	II
Slagvastheid	IK10

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Cable management enclosure Series J, dotted, 2 doors, size 2 H=1100 W=1130 D=320mm, door opening angle 180°		IG009405
Optionele toebehoren		
Mountingplate for IG009405, H=985 W=1035 D=6mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009445
plastic base frame sizes 2/S6 1200/400 plastic base frame serving as a foundation for plinth		IG790330
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 2/S6/310 (absorption mat)		IG793820
Plinth Polyester Series J size 2, RAL7035 H=905 W=1110 D=310mm		IG009315
Adapter bar for KVS - IG009405, size 2 (PU=2 pcs.) Pre-cut with M6 machine tap bit		IG009465

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Optionele toebehoren		
Modular chassis 4-21K, 7-rows, complete		IL148421-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009405 & IG009505		IG009425
H=288 W=1088 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 2		
For IG009405 and IG009505, 10 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	9610	IG0090312
Copper busbar, 30x10mm for Size 2		
For IG009405 and IG009505, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	2810	IG009P312
Copper busbar, 40x10mm for Size 2		
For IG009405 and IG009505, 10 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	13010	IG0090412
Afdekking 100mm voor railsysteem 185mm		ISA05360
For mounting on insert nuts M12		
Halfcilinder draaiend H36000 3 sleutels		IL900381
Voor IU001225/ IU001903		
Halfcilinder draaiend H36000 3 sleutels		IL900381
Voor IU001225/ IU001903		