

Datenblatt für Artikel: IG009502--

Cable management enclosure Series J, 1 door, size 0

dotted surface, H=850 W=605 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technische Daten

Breedte (mm)	605,00
Hoogte (mm)	850,00

Technische Daten - Fortsetzung

Diepte (mm)	320,00
Nettogewicht (kg)	20,52
Beschermingsgraad	IP44
Beschermingsklasse	II
Slagvastheid	IK10
Uitvoering	Polyester glasvezelversterkt kunststof
Kleur	RAL 7035
Breedte (mm)	605
Hoogte (mm)	850
Diepte (mm)	320
Aantal deuren	1
Sluitingen	Zwenkgreep met halve cilinder

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Cable management enclosure Series J, 1 door, size 0 dotted surface, H=850 W=605 D=320mm, door opening angle 180°		IG009502
Optionele toebehoren		
Mountingplate for IG009502, H=735 W=500 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009552
plastic base frame sizes 00/S3 and 0/S4 600/400 plastic base frame serving as a foundation for plinth		IG790328
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 0/S4/310 (absorption mat)		IG793818
Plinth Polyester Series J size 0, RAL7035 H=902 W=585 D=310mm		IG009312
Ground plate for Wall mounting for IG009302 H=285 W=560 D=4mm		IG009322
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009402 & IG009502 H=288 W=563 D=4mm		IG009422

Artikeltabelle

BEZEICHNUNG	KUPFERGEWICHT (kg/km)	BEST.NR.
Optionele toebehoren		
Copper busbar Set 4-pole, 30x10mm for Size 0 For IG009402 and IG009502, 5 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	4550	IG0090310
Copper busbar, 30x10mm for Size 0 For IG009402 and IG009502, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1440	IG009P310
Afdekking 100mm voor railsysteem 185mm For mounting on insert nuts M12		ISA05360
Halfcilinder draaiend H36000 3 sleutels Voor IU001225/ IU001903		IL900381