

Datenblatt für Artikel: IG009503--

# Cable management enclosure Series J, 1 door, size 1

dotted surface, H=850 W=800 D=320mm, door opening angle 180°



## SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

### Mögliche Ausbaupvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



## Technische Daten

|              |        |
|--------------|--------|
| Breedte (mm) | 800,00 |
| Hoogte (mm)  | 850,00 |

## Technische Daten - Fortsetzung

|                    |                                        |
|--------------------|----------------------------------------|
| Diepte (mm)        | 320,00                                 |
| Nettogewicht (kg)  | 24,20                                  |
| Beschermingsgraad  | IP44                                   |
| Beschermingsklasse | II                                     |
| Slagvastheid       | IK10                                   |
| Uitvoering         | Polyester glasvezelversterkt kunststof |
| Kleur              | RAL 7035                               |
| Breedte (mm)       | 800                                    |
| Hoogte (mm)        | 850                                    |
| Diepte (mm)        | 320                                    |
| Aantal deuren      | 1                                      |
| Sluitingen         | Zwenkgreep met halve cilinder          |

## Artikeltabelle

| BEZEICHNUNG                                                                                                                       | KUPFERGEWICHT (kg/km) | BEST.NR. |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------|----------|
| Cable management enclosure Series J, 1 door, size 1<br>dotted surface, H=850 W=800 D=320mm, door opening angle 180°               |                       | IG009503 |
| <b>Optionele toebehoren</b>                                                                                                       |                       |          |
| Mountingplate for IG009503, H=735 W=680 D=5mm<br>including fastening screws, mounting plate made of melamine-laminated hard paper |                       | IG009553 |
| plastic base frame sizes 1/S5 800/400<br>plastic base frame serving as a foundation for plinth                                    |                       | IG790329 |
| base filler - hydrophobic<br>100 liter bag, water-repellent - hydrophobic                                                         |                       | IG790333 |
| base filler expanded clay 4-8mm round 50L<br>water-absorbing - expanded clay, 50 liter bag                                        |                       | IG790570 |
| foam insert size 1/S5/310 (absorption mat)                                                                                        |                       | IG793819 |
| Plinth Polyester Series J size 1, RAL7035<br>H=902 W=780 D=310mm                                                                  |                       | IG009313 |
| Ground plate for Wall mounting for IG009303<br>H=285 W=755 D=4mm                                                                  |                       | IG009323 |
| Wall mounting kit Size 00-2, for IG0094 und IG0095                                                                                |                       | IG009500 |
| Ground plate for Wall mounting for IG009403 & IG009503<br>H=288 W=758 D=4mm                                                       |                       | IG009423 |

## Artikeltabelle

| BEZEICHNUNG                                                                                                                                                                      | KUPFERGEWICHT (kg/km) | BEST.NR.  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------|
| <b>Optionele toebehoren</b>                                                                                                                                                      |                       |           |
| Copper busbar Set 4-pole, 30x10mm for Size 1<br>For IG009403 and IG009503, 7 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers | 6520                  | IG0090311 |
| Copper busbar, 30x10mm for Size 1<br>For IG009403 and IG009503, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers                                               | 1980                  | IG009P311 |
| Afdekking 100mm voor railsysteem 185mm<br>For mounting on insert nuts M12                                                                                                        |                       | ISA05360  |
| Halfcilinder draaiend H36000 3 sleutels<br>Voor IU001225/ IU001903                                                                                                               |                       | IL900381  |