


## Multi-level terminal block PT 4-PE/3L

Push-in connection, 0.2 - 6 mm<sup>2</sup>, AWG: 24 - 10, width: 6.2 mm, height: 95.4 mm, grey, NS 35/7.5, NS 35/15



### Technische Daten

|                                                                                     |                   |
|-------------------------------------------------------------------------------------|-------------------|
| Diepte (mm)                                                                         | 95,40             |
| Breedte (mm)                                                                        | 6,20              |
| Hoogte (mm)                                                                         | 104,40            |
| Nettogewicht (kg)                                                                   | 0,04              |
| EAN CODE                                                                            | 4046356915472     |
| Stroomwarmteverliezen (W)                                                           | 1,02              |
| Omgevingstemperatuur min. (°C)                                                      | -40               |
| Omgevingstemperatuur max. (°C)                                                      | 120               |
| Basisbeschrijving                                                                   | Klemmen           |
| Systeem                                                                             | Push-In           |
| Productgamma                                                                        | PT                |
| Productgroep                                                                        | Meer-etageklemmen |
| Maximale aansluitcapaciteit vaste geleiders (mm <sup>2</sup> )                      | 6                 |
| Maximale aansluitcapaciteit soepele geleiders (mm <sup>2</sup> )                    | 4                 |
| Maximale aansluitcapaciteit soepele geleiders met adereindhulzen (mm <sup>2</sup> ) | 4                 |
| Minimale aansluitcapaciteit vaste geleiders (mm <sup>2</sup> )                      | 0,20              |
| Minimale aansluitcapaciteit soepele geleiders (mm <sup>2</sup> )                    | 0,20              |

## Technische Daten - Fortsetzung

|                                                                                     |       |
|-------------------------------------------------------------------------------------|-------|
| Minimale aansluitcapaciteit soepele geleiders met adereindhulzen (mm <sup>2</sup> ) | 0,25  |
| Aansluitcapaciteit (mm <sup>2</sup> )                                               | 4     |
| Kleur                                                                               | Grijs |
| Nominale stroom (A)                                                                 | 26    |

## Artikeltabelle

| BEZEICHNUNG                                                                                                    | BEST.NR.   |
|----------------------------------------------------------------------------------------------------------------|------------|
| Multi-level terminal block PT 4-PE/3L                                                                          | IP3210442  |
| Push-in connection, 0.2 - 6 mm², AWG: 24 - 10, width: 6.2 mm, height: 95.4 mm, grey, NS 35/7.5, NS 35/15       |            |
| Optionele toebehoren                                                                                           |            |
| End bracket CLIPFIX 15, to be snapped onto NS 15 DIN rail                                                      | IP3022263  |
| Snap-on end bracket, color: gray                                                                               |            |
| End bracket CLIPFIX 35-5, for NS 35/7,5 or NS 35/15                                                            | IP3022276  |
| Quick mounting end clamp, with marking option, width: 5.15 mm, color: gray                                     |            |
| End bracket CLIPFIX 35, for NS 35/7,5 DIN rail or NS 35/15                                                     | IP3022218  |
| Quick mounting end clamp, with marking option, width: 9.5 mm, color: gray                                      |            |
| End bracket E/UK                                                                                               | IP1201442  |
| End clamp, Width: 9.5 mm, Height: 35.3 mm, Length: 50.5 mm, Color: gray                                        |            |
| End bracket E/UK 1                                                                                             | IP1201413  |
| End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray |            |
| End bracket E/MBK                                                                                              | IP1401637  |
| End clamp, width: 6.2 mm, color: gray                                                                          |            |
| End bracket E/MK 1                                                                                             | IP1421659  |
| End clamp width: 6 mm, color: gray                                                                             |            |
| End bracket E/NS 35 N                                                                                          | IP0800886  |
| End clamp, width: 9.5 mm, color: gray                                                                          |            |
| Zack marker strip ZB 6, consecutive numbers 1-10                                                               | IP10510161 |
| Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         |            |
| Zack marker strip ZB 6, consecutive numbers 11-20                                                              | IP10510162 |
| Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         |            |
| Zack marker strip ZB 6, consecutive numbers 21-30                                                              | IP10510163 |
| Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         |            |

## Artikeltabelle

| BEZEICHNUNG                                                                                                                                                         | BEST.NR.   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>Optionele toebehoren</b>                                                                                                                                         |            |
| Zack marker strip ZB 6, consecutive numbers 31-40<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         | IP10510164 |
| Zack marker strip ZB 6, consecutive numbers 41-50<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         | IP10510165 |
| Zack marker strip ZB 6, consecutive numbers 51-60<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         | IP10510166 |
| Zack marker strip ZB 6, consecutive numbers 61-70<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         | IP10510167 |
| Zack marker strip ZB 6, consecutive numbers 71-80<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         | IP10510168 |
| Zack marker strip ZB 6, consecutive numbers 81-90<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm         | IP10510169 |
| Zack marker strip ZB 6, consecutive numbers 91-100<br>Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm        | IP1051016H |
| Zack marker strip flat ZBF 6, blank<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm                      | IP0808710  |
| Zack marker strip flat ZBF 6, consecutive numbers 1-10<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm   | IP08087491 |
| Zack marker strip flat ZBF 6, consecutive numbers 11-20<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087492 |
| Zack marker strip flat ZBF 6, consecutive numbers 21-30<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087493 |
| Zack marker strip flat ZBF 6, consecutive numbers 31-40<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087494 |
| Zack marker strip flat ZBF 6, consecutive numbers 41-50<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087495 |
| Zack marker strip flat ZBF 6, consecutive numbers 51-60<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087496 |
| Zack marker strip flat ZBF 6, consecutive numbers 61-70<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087497 |
| Zack marker strip flat ZBF 6, consecutive numbers 71-80<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087498 |
| Zack marker strip flat ZBF 6, consecutive numbers 81-90<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm  | IP08087499 |
| Zack marker strip flat ZBF 6, consecutive numbers 91-100<br>Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm | IP0808749H |
| End cover D-PT 4-PE/3L<br>End cover, length: 104.5 mm, width: 2.2 mm, height: 92.1 mm, color: grey                                                                  | IP3210443  |

## Artikeltabelle

| BEZEICHNUNG                                                                                                                                           | BEST.NR.  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| <b>Optionele toebehoren</b>                                                                                                                           |           |
| Plug-in bridge FBS 2-6                                                                                                                                | IP3030336 |
| Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 10.7 mm, poles: 2, color: red                                                                    |           |
| Plug-in bridge FBS 3-6                                                                                                                                | IP3030242 |
| Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 16,9 mm, poles: 3, color: red                                                                    |           |
| Plug-in bridge FBS 4-6                                                                                                                                | IP3030255 |
| Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 23,1 mm, poles: 4, color: red                                                                    |           |
| Plug-in bridge FBS 5-6                                                                                                                                | IP3030349 |
| Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 29.3 mm, poles: 5, color: red                                                                    |           |
| Plug-in bridge FBS 10-6                                                                                                                               | IP3030271 |
| Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 60.3 mm, poles: 10, color: red                                                                   |           |
| Plug-in bridge FBS 20-6                                                                                                                               | IP3030365 |
| Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 122.3 mm, poles: 20, color: red                                                                  |           |
| Plug-in bridge FBSR 2-6                                                                                                                               | IP3033715 |
| Plug-in bridge, pitch: 6.2 mm, poles: 2, color: red                                                                                                   |           |
| Plug-in bridge FBSR 3-6                                                                                                                               | IP3001594 |
| Plug-in bridge, pitch: 6.2 mm, poles: 3, color: red                                                                                                   |           |
| Plug-in bridge FBSR 4-6                                                                                                                               | IP3001595 |
| Plug-in bridge, pitch: 6.2 mm, poles: 4, color: red                                                                                                   |           |
| Plug-in bridge FBSR 5-6                                                                                                                               | IP3001596 |
| Plug-in bridge, pitch: 6.2 mm, poles: 5, color: red                                                                                                   |           |
| Plug-in bridge FBSR 10-6                                                                                                                              | IP3033716 |
| Plug-in bridge, pitch: 6.2 mm, poles: 10, color: red                                                                                                  |           |
| Screwdriver 0.6 x 3.5 ( SZF 1-0.6X3.5)                                                                                                                | IP1204517 |
| Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip |           |