


Feed-through terminal block PTU 4-TWIN

Push-in connection, screw connection, cross section: 0.2 mm² - 6 mm², AWG : 24- 12, width: 6.2 mm, grey



Technische Daten

Diepte (mm)	42,80
Breedte (mm)	6,20
Hoogte (mm)	69,30
Nettogewicht (kg)	0,01
EAN CODE	4046356802116
Stroomwarmteverliezen (W)	1,02
Omgevingstemperatuur min. (°C)	-40
Omgevingstemperatuur max. (°C)	120
Basisbeschrijving	Klemmen
Systeem	Push-In
Productgamma	PT
Productgroep	Dubbele rijklemmen
Maximale aansluitcapaciteit vaste geleiders (mm ²)	6
Maximale aansluitcapaciteit soepele geleiders (mm ²)	4
Maximale aansluitcapaciteit soepele geleiders met adereindhulzen (mm ²)	4
Minimale aansluitcapaciteit vaste geleiders (mm ²)	0,20
Minimale aansluitcapaciteit soepele geleiders (mm ²)	0,20

Technische Daten - Fortsetzung

Minimale aansluitcapaciteit soepele geleiders met adereindhulzen (mm ²)	0,25
Aansluitcapaciteit (mm ²)	4
Kleur	Grijs
Nominale stroom (A)	32

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Feed-through terminal block PTU 4-TWIN	IP3211859
Push-in connection, screw connection, cross section: 0.2 mm² - 6 mm², AWG : 24- 12, width: 6.2 mm, grey	
Optionele toebehoren	
End bracket CLIPFIX 15, to be snapped onto NS 15 DIN rail	IP3022263
Snap-on end bracket, color: gray	
End bracket CLIPFIX 35-5, for NS 35/7,5 or NS 35/15	IP3022276
Quick mounting end clamp, with marking option, width: 5.15 mm, color: gray	
End bracket CLIPFIX 35, for NS 35/7,5 DIN rail or NS 35/15	IP3022218
Quick mounting end clamp, with marking option, width: 9.5 mm, color: gray	
End bracket E/UK	IP1201442
End clamp, Width: 9.5 mm, Height: 35.3 mm, Length: 50.5 mm, Color: gray	
End bracket E/UK 1	IP1201413
End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray	
End bracket E/MBK	IP1401637
End clamp, width: 6.2 mm, color: gray	
End bracket E/MK 1	IP1421659
End clamp width: 6 mm, color: gray	
End bracket E/NS 35 N	IP0800886
End clamp, width: 9.5 mm, color: gray	
Zack marker strip ZB 6, consecutive numbers 1-10	IP10510161
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	
Zack marker strip ZB 6, consecutive numbers 11-20	IP10510162
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	
Zack marker strip ZB 6, consecutive numbers 21-30	IP10510163
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
Zack marker strip ZB 6, consecutive numbers 31-40 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510164
Zack marker strip ZB 6, consecutive numbers 41-50 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510165
Zack marker strip ZB 6, consecutive numbers 51-60 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510166
Zack marker strip ZB 6, consecutive numbers 61-70 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510167
Zack marker strip ZB 6, consecutive numbers 71-80 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510168
Zack marker strip ZB 6, consecutive numbers 81-90 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510169
Zack marker strip ZB 6, consecutive numbers 91-100 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP1051016H
Zack marker strip flat ZBF 6, blank Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP0808710
Zack marker strip flat ZBF 6, consecutive numbers 1-10 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087491
Zack marker strip flat ZBF 6, consecutive numbers 11-20 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087492
Zack marker strip flat ZBF 6, consecutive numbers 21-30 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087493
Zack marker strip flat ZBF 6, consecutive numbers 31-40 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087494
Zack marker strip flat ZBF 6, consecutive numbers 41-50 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087495
Zack marker strip flat ZBF 6, consecutive numbers 51-60 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087496
Zack marker strip flat ZBF 6, consecutive numbers 61-70 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087497
Zack marker strip flat ZBF 6, consecutive numbers 71-80 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087498
Zack marker strip flat ZBF 6, consecutive numbers 81-90 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087499
Zack marker strip flat ZBF 6, consecutive numbers 91-100 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP0808749H
End cover D-PTU 4-TWIN End cover, length: 69.3 mm, width: 2.2 mm, color: grey	IP3211863

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
Plug-in bridge FBS 2-6	IP3030336
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 10.7 mm, poles: 2, color: red	
Plug-in bridge FBS 3-6	IP3030242
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 16,9 mm, poles: 3, color: red	
Plug-in bridge FBS 4-6	IP3030255
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 23,1 mm, poles: 4, color: red	
Plug-in bridge FBS 5-6	IP3030349
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 29.3 mm, poles: 5, color: red	
Plug-in bridge FBS 10-6	IP3030271
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 60.3 mm, poles: 10, color: red	
Plug-in bridge FBS 20-6	IP3030365
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 122.3 mm, poles: 20, color: red	
Plug-in bridge FBSR 2-6	IP3033715
Plug-in bridge, pitch: 6.2 mm, poles: 2, color: red	
Plug-in bridge FBSR 3-6	IP3001594
Plug-in bridge, pitch: 6.2 mm, poles: 3, color: red	
Plug-in bridge FBSR 4-6	IP3001595
Plug-in bridge, pitch: 6.2 mm, poles: 4, color: red	
Plug-in bridge FBSR 5-6	IP3001596
Plug-in bridge, pitch: 6.2 mm, poles: 5, color: red	
Plug-in bridge FBSR 10-6	IP3033716
Plug-in bridge, pitch: 6.2 mm, poles: 10, color: red	
Screwdriver 0.6 x 3.5 (SZF 1-0.6X3.5)	IP1204517
Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip	