

Datenblatt für Artikel: KT188040--

# Compact enclosure 1 door IP65 H=1800 W=800 D=400 mm

sheet steel, RAL7035, with mounting plate, four-point rod lock with push-pull handle



## SCHRACK-Info

- **Material** : Corpus: 1.5 mm galvanised sheet steel. Doors: Single door and double door: 1.5 mm sheet steel. Rear panel: 1.2 mm sheet steel
- **Mounting plate** : 3 mm galvanised sheet steel. Double folded, mounted in the enclosure, fully adjustable in depth in 25 mm increments
- **Bottom plates** : 1.5 mm galvanised sheet steel, consists of
  - two-part bottom plate at depth 300 mm
  - three-part bottom plate at depths 400 and 500 mm
- **Frame** : Folded and seam welded reversed open profile with 25 mm hole pattern according to DIN 43660. Including integrated external hole pattern
- **Door** : On single door enclosures, the door is mounted on four double-sided hinges for right-hand opening (= hinged right). Doors for left-hand opening (= hinged left) have to be ordered separately. On double door enclosures, hinges are not reversible. All door panels include the door mounting frame with 25 mm hole pattern. The left Z-wing is locked separately with an inner three-point lock
- **Lock** : Four-point rod lock with push-pull handle with spring adjustment and half cylinder lock 5333 (identical key), does not slide inward. The standard lock can be exchanged for profile half cylinder (DIN cylinder) and other inserts from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Rear panel** : Mounted with M6 torx screws. Replacement against additional door from the back side is possible. For 1600 mm wide enclosures the rear panel is divided
- **Roof panel** : Removable


- **Earthing** : All panels are earthed through their fittings and are equipped with a separate earthing stud
- **Degree of protection** : Single door IP65 and double door IP54
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL7035 (Light grey)
- **Delivery includes** : Enclosure with door, rear panel, roof panel, bottom plates, mounting plate with fixing material for the nearest position of the rear panel and earthing studs. Delivered on a pallet with equal width as the enclosure



## Technische Daten

|                                 |                           |
|---------------------------------|---------------------------|
| Breedte (mm)                    | 800,00                    |
| Hoogte (mm)                     | 1.800,00                  |
| Diepte (mm)                     | 400,00                    |
| Nettogewicht (kg)               | 123,70                    |
| Omgevingstemperatuur min. (°C)  | -20                       |
| Omgevingstemperatuur max. (°C)  | 70                        |
| Beschermingsgraad               | IP65                      |
| Beschermingsklasse              | I                         |
| Uitvoering                      | Plaatstaal                |
| Kleur                           | RAL 7035                  |
| Breedte (mm)                    | 800                       |
| Hoogte (mm)                     | 1800                      |
| Diepte (mm)                     | 400                       |
| Kast plaatdikte (mm)            | 1,50                      |
| Montageplaat                    | Plaatstaal gegalvaniseerd |
| Montageplaat dikte (mm)         | 3                         |
| Montageplaat breedte (mm)       | 688                       |
| Montageplaat hoogte (mm)        | 1688                      |
| Deur dikte (mm)                 | 1,50                      |
| Bodemplatten aantal             | 3                         |
| Draagvermogen per deur (kg)     | 50                        |
| Aantal deuren                   | 1                         |
| Breedte bodemplaat (mm)         | 555                       |
| Load Capacity Roof Panel (kg)   | 40                        |
| Load Capacity Side Panel (kg)   | 90                        |
| Product                         | Compact kast              |
| Draagvermogen totaal (kg)       | 1200                      |
| Draagvermogen montageplaat (kg) | 500                       |
| Stroomwarmteverliezen (W)       | -724,00                   |

## Maattekening: Compact enclosure 1 door IP65 H=1800 W=800 D=400 mm



### Artikeltabelle

| BEZEICHNUNG                                                                          | BEST.NR.   |
|--------------------------------------------------------------------------------------|------------|
| Compact enclosure 1 door IP65 H=1800 W=800 D=400 mm                                  | KT188040   |
| sheet steel, RAL7035, with mounting plate, four-point rod lock with push-pull handle |            |
| <b>Optionele toebehoren</b>                                                          |            |
| LED ligh for EC, infra (not available in this country)                               | IU006519CZ |
| WSA Sokkel 4 hoeken H=100mm ABS RAL7012                                              | ATSOC104   |
| Set 4 hoeken, panelen breedtedelen en dieptedelen zijn apart te bestellen            |            |
| WSA Sokkel 4 hoeken H=200mm ABS RAL7012                                              | ATSOC204   |
| Set 4 hoeken, panelen breedtedelen en dieptedelen zijn apart te bestellen            |            |
| WSA Sokkel 2 dieptedelen DxH 400x100mm RAL7012                                       | ATSOT041   |
| Set 2 panelen dieptedelen, hoeken en breedtedelen zijn apart te bestellen            |            |
| WSA Sokkel 2 breedtedelen BxH 800x100mm RAL7012                                      | ATSOB081   |
| Levering, set van 2 panelen breedte vooraan en achteraan                             |            |
| AC Hijsogen verzinkt M12 (set 4stk.)                                                 | ACLE9301   |
| Planhouder A4 zelfklevend                                                            | ASDRA400   |
| HxBxD 235x264x33mm                                                                   |            |
| DIN-rail TS35 gegalvaniseerd 3000x35x7,5mm                                           | BK14004--B |
| De opgegeven prijs is per stuk.                                                      |            |
| DIN-rail TS35 geperforeerd gegalvaniseerd 2000x35x7,5mm                              | BK14005--A |
| De opgegeven prijs is per stuk.                                                      |            |
| DIN-rail TS35 gegalvaniseerd 2000x35x15mm                                            | IL14035--A |
| De opgegeven prijs is per stuk.                                                      |            |

## Artikeltabelle

| BEZEICHNUNG                                            | BEST.NR. |
|--------------------------------------------------------|----------|
| <b>Optionele toebehoren</b>                            |          |
| DIN-rail TS35 geperforeerd gegalvaniseerd 2000x35x15mm | IL14037  |
| De opgegeven prijs is per stuk.                        |          |