

Datenblatt für Artikel: LI1000788-

# ALAMEA LED Recessed ceiling luminaire, black, 3000K, 45W



## Technische Daten

|                             |                           |
|-----------------------------|---------------------------|
| Net length (mm)             | 246,00                    |
| Net width (mm)              | 156,00                    |
| Net height (mm)             | 113,00                    |
| Net weight (kg)             | 2,20                      |
| Cut-out size (mm)           | 225x130                   |
| Mounting                    | recessed mounting ceiling |
| Colour                      | Black                     |
| Material                    | Aluminum<br>Glass         |
| Manufacturer                | 03-SLV                    |
| Operation current mA (mA)   | 1000                      |
| Watt (W)                    | 45                        |
| System efficiency (lm/W)    | 80                        |
| Colour temperature (K)      | 3000                      |
| Colour rendering index (Ra) | 90                        |
| Luminous flux (lm)          | 3600                      |
| Live time                   | 35.000h                   |
| Protection class            | III                       |

## Technische Daten - Fortsetzung

|                         |              |
|-------------------------|--------------|
| Energy efficiency class | A++   A+   A |
| Mounting depth (mm)     | 113          |
| Illuminant incl.        | yes          |
| LxWxH mm                | 246x156x113  |
| Cut-out size mm         | 225x130      |

## Artikeltabelle

| BEZEICHNUNG                                                                      | BEST.NR.  |
|----------------------------------------------------------------------------------|-----------|
| ALAMEA LED Recessed ceiling luminaire, black, 3000K, 45W                         | LI1000788 |
| <b>Optional Accessories</b>                                                      |           |
| LED driver, 1000mA, 40W, dimmable                                                | LI1001115 |
| TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable<br>inkl. Cable relief | LI464032  |
| LED-Driver, 40W, 1000mA, incl. strain relief                                     | LI464170  |