

Datenblatt für Artikel: LI1003728-

NUMINOS XL DL 37,4W 3550lm 3000K 55° 1050mA LED zwart/wit

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Produktinfo

NUMINOS is the perfectly coordinated lighting system from SLV, combining function, design and technology. With a wide range of down- and spotlights you will experience a thousand possibilities for light design. This includes also NUMINOS® MOVE DL XL, which as recessed ceiling lights through best processing- and light quality stands out. Ideal for a discreet, modern and space-saving lighting, which directs the accent on objects or the room. The recessed ceiling lights impress with a power consumption of 37.4 Watt, light output of 3550 lumens, color temperature of 3000 Kelvin and a color rendering index of 90. The installation is completed by simply turning the handle. When do you decide for NUMINOS® from SLV?

Technische Daten

Lichtstroom (lm)	3550
Lichtkleur	Warmwit
Kleurtemperatuur (K)	3000
Kleurweergave-index (Ra)	≥90
Levensduur	50.000h
Regelen lichtintensiteit	Afhankelijk van driver Ja
Beschermingsklasse	III

Technische Daten - Fortsetzung

Beschermingsgraad	IP20
Type verlichting	Inbouw plafondverlichting
Lichtmiddel inbegrepen	Inbegrepen
Lampvoet	LED
Stralingshoek (°)	120
Vermogen (W)	37,40
Bedrijfsstroom mA (mA)	1050
Boring voor inbouw (mm)	Ø 175
Inbouw diepte (mm)	130
Afwerking	Wit Zwart
Uitvoering	Aluminium Polycarbonaat
Lengte (mm)	190
Breedte (mm)	190
Hoogte (mm)	118
Diameter (mm)	190
Optionele toebehoren	LI1004059-;LI1004066-;LI1004071-;LI1004798-;LI1004799-;LI1004800-;LI1004801-;LI1006151-;LI1006152-;LI1006153-;LI1006154-
LxBxH (mm)	190x190x118
ØxH (mm)	190x118
Uitsnijding (mm)	Ø 175

Artikeltabelle

BEZEICHNUNG	BEST.NR.
NUMINOS XL DL 37,4W 3550lm 3000K 55° 1050mA LED zwart/wit	LI1003728
Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	
Optionele toebehoren	
LED Driver 40W multi mA	LI1004059
LED Driver	
LED Driver 28-40W 1000mA PHASE	LI1004066
LED Driver	
LED Driver 42-50W 1050mA DALI	LI1004071
LED Driver	
NUMINOS XL Diffusor Ellipse W LED IP20 transparant	LI1004798
NUMINOS XL Diffusor Prisma W LED IP20 transparant	LI1004799

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
NUMINOS XL Diffusor Frosted W LED IP20 frosted	L11004800
NUMINOS XL Diffusor Wabe W LED zwart	L11004801
Numinos® XL montage frame, rond 240/180mm zwart Mounting frame/socket	L11006151
Numinos® XL montage frame, rond 240/180mm wit Mounting frame/socket	L11006152
Numinos® XL montage frame, vierk. 240/180mm zwart Mounting frame/socket	L11006153
Numinos® XL montage frame, vierk. 240/180mm wit Mounting frame/socket	L11006154