

Datenblatt für Artikel: LI1008606-

LED-Paneel C 1200x300mm 34W 3000K/ 4000K Ra>90 UGR≤19

mounting spring and suspension rope must be ordered separately



Technische Daten

Netto lengte (mm)	1.195,00
Breedte (mm)	295,00
Hoogte (mm)	28,00
Nettogewicht (kg)	1,80
Type verlichting	LED-Paneel
Kleur	Wit
Uitvoering	Aluminium
Stralingshoek (°)	90
Verblindingsfactor (UGR)	19
Nominale werkspanning AC (V)	220-240
Lampvoet	LED
Lichtrendement (lm/W)	123,53
Vermogen (W)	34
Lichtkleur	Warmwit Neutraalwit
Kleurtemperatuur (K)	4000 3000

Technische Daten - Fortsetzung

Kleurweergave-index (Ra)	90
Lichtstroom (lm)	4200 4400
Levensduur	70000
Beschermingsklasse	II
Slagvastheid	IK02
LxBxH (mm)	1195x295x28

Artikeltabelle

BEZEICHNUNG	BEST.NR.
LED-Paneel C 1200x300mm 34W 3000K/ 4000K Ra>90 UGR≤19 mounting spring and suspension rope must be ordered separately	LI1008606
Noodzakelijke toebehoren	
PANEL C 4x Montagefedern	LI1008610
PANEL C Abhängeseil L: 150 cm	LI1008609