

Datenblatt für Artikel: LI1009053-

# GRIP! S Deckeneinbaul. PHASE 3000K 29°

## IP20 zyl ws/sw

recessed ceiling light



### Technische Daten

|                          |           |
|--------------------------|-----------|
| Netto lengte (mm)        | 135,00    |
| Breedte (mm)             | 30,00     |
| Hoogte (mm)              | 42,00     |
| Netto diameter (mm)      | 30,00     |
| Nettogewicht (kg)        | 0,22      |
| Kleur                    | Wit       |
| Uitvoering               | Staal     |
| Stralingshoek (°)        | 29        |
| Verblindingsfactor (UGR) | 25        |
| Kleurtemperatuur (K)     | 3000      |
| Kleurweergave-index (Ra) | 90        |
| Lichtstroom (lm)         | 620       |
| Levensduur               | 50000     |
| Beschermingsklasse       | II        |
| Beschermingsgraad        | IP20      |
| ØxH (mm)                 | 30x42     |
| LxBxH (mm)               | 135x30x42 |

| BEZEICHNUNG                                                                     | BEST.NR.  |
|---------------------------------------------------------------------------------|-----------|
| GRIP! S Deckeneinbaul. PHASE 3000K 29° IP20 zyl ws/sw<br>recessed ceiling light | LI1009053 |