

Datenblatt für Artikel: LI1009091 -

# GRIP! M Deckeneinbaul. PHASE 3000K 42°

## IP20 zyl gold/sw

recessed ceiling light



### Technische Daten

|                          |           |
|--------------------------|-----------|
| Netto lengte (mm)        | 182,00    |
| Breedte (mm)             | 43,00     |
| Hoogte (mm)              | 64,00     |
| Netto diameter (mm)      | 43,00     |
| Nettogewicht (kg)        | 0,36      |
| Kleur                    | Zwart     |
| Uitvoering               | Staal     |
| Stralingshoek (°)        | 42        |
| Kleurtemperatuur (K)     | 3000      |
| Kleurweergave-index (Ra) | 90        |
| Lichtstroom (lm)         | 2110      |
| Levensduur               | 50000     |
| Beschermingsklasse       | II        |
| Beschermingsgraad        | IP20      |
| ØxH (mm)                 | 43x64     |
| LxBxH (mm)               | 182x43x64 |

| BEZEICHNUNG                                                                       | BEST.NR.  |
|-----------------------------------------------------------------------------------|-----------|
| GRIP! M Deckeneinbaul. PHASE 3000K 42° IP20 zyl gold/sw<br>recessed ceiling light | LI1009091 |