

Datenblatt für Artikel: LI1009328-

# NUMINOS MOVE XS Deckeneinbaul. 2700K

## 40° IP20 rund sw

recessed ceiling light



### Technische Daten

|                          |           |
|--------------------------|-----------|
| Netto lengte (mm)        | 80,00     |
| Breedte (mm)             | 80,00     |
| Hoogte (mm)              | 53,00     |
| Netto diameter (mm)      | 80,00     |
| Nettogewicht (kg)        | 0,11      |
| Kleur                    | Zwart     |
| Uitvoering               | Aluminium |
| Stralingshoek (°)        | 40        |
| Verblindingsfactor (UGR) | 22        |
| Vermogen (W)             | 6,90      |
| Kleurtemperatuur (K)     | 2700      |
| Kleurweergave-index (Ra) | 90        |
| Lichtstroom (lm)         | 900       |
| Levensduur               | 50000     |
| Beschermingsklasse       | III       |
| Beschermingsgraad        | IP20      |
| ØxH (mm)                 | 80x53     |

## Technische Daten - Fortsetzung

LxBxH (mm)

| 80x80x53

| BEZEICHNUNG                                                                     | BEST.NR.  |
|---------------------------------------------------------------------------------|-----------|
| NUMINOS MOVE XS Deckeneinbaul. 2700K 40° IP20 rund sw<br>recessed ceiling light | LI1009328 |