

Datenblatt für Artikel: LI1010009-

# NUMINOS MOVE XL Deckeneinbaul. 4000K

## 20° IP20 rund sw/ws

recessed ceiling light



### Technische Daten

|                          |           |
|--------------------------|-----------|
| Netto lengte (mm)        | 190,00    |
| Breedte (mm)             | 190,00    |
| Hoogte (mm)              | 116,00    |
| Netto diameter (mm)      | 190,00    |
| Nettogewicht (kg)        | 0,63      |
| Kleur                    | Zwart     |
| Uitvoering               | Aluminium |
| Stralingshoek (°)        | 20        |
| Verblindingsfactor (UGR) | 19        |
| Vermogen (W)             | 24        |
| Kleurtemperatuur (K)     | 4000      |
| Kleurweergave-index (Ra) | 90        |
| Lichtstroom (lm)         | 3800      |
| Levensduur               | 50000     |
| Beschermingsklasse       | III       |
| Beschermingsgraad        | IP20      |
| ØxH (mm)                 | 190x116   |

## Technische Daten - Fortsetzung

LxBxH (mm)

| 190x190x116

| BEZEICHNUNG                                                                        | BEST.NR.  |
|------------------------------------------------------------------------------------|-----------|
| NUMINOS MOVE XL Deckeneinbaul. 4000K 20° IP20 rund sw/ws<br>recessed ceiling light | LI1010009 |