

Datenblatt für Artikel: LI1010286-

# LALU® Pendell. Einbau LED Base 2700/3000K 40° PHASE sw

pendant light



## Technische Daten

|                          |              |
|--------------------------|--------------|
| Netto lengte (mm)        | 34,50        |
| Breedte (mm)             | 34,50        |
| Hoogte (mm)              | 107,00       |
| Netto diameter (mm)      | 34,50        |
| Nettogewicht (kg)        | 0,34         |
| Kleur                    | Zwart        |
| Uitvoering               | Aluminium    |
| Stralingshoek (°)        | 40           |
| Kleurtemperatuur (K)     | 2700<br>3000 |
| Kleurweergave-index (Ra) | 90           |
| Lichtstroom (lm)         | 700<br>800   |
| Levensduur               | 50000        |
| Beschermingsklasse       | II           |
| Beschermingsgraad        | IP20         |
| ØxH (mm)                 | 35x107       |

## Technische Daten - Fortsetzung

LxBxH (mm) | 35x35x107

| BEZEICHNUNG                                                             | BEST.NR.  |
|-------------------------------------------------------------------------|-----------|
| LALU® Pendell. Einbau LED Base 2700/3000K 40° PHASE sw<br>pendant light | LI1010286 |