

Datenblatt für Artikel: LI111011 --

OUT 65 downlight, GX5,3, max. 35W, white



Technische Daten

Net height (mm)	120,00
Net diameter (mm)	84,00
Net weight (kg)	0,17
Cut-out size (mm)	Ø72
Luminaire type	Recessed ceiling luminaire Recessed wall luminaire
Mounting	recessed wall mounting recessed mounting ceiling
Colour	White
Material	Aluminum Glass
Manufacturer	03-SLV
Operating voltage AC (V)	12
Operating voltage DC (V)	12
Light source	Low voltage halogen - reflector lamp
Lamp holder	MR16
Socket	GX5,3
Watt (W)	35
Number of lamps	1
Protection class	III

Technische Daten - Fortsetzung

IP Rating	IP65
Mounting depth (mm)	130
ØxH mm	84x120
Diameter (mm)	85
Cut-out size mm	Ø72

Artikeltabelle

BEZEICHNUNG	BEST.NR.
OUT 65 downlight, GX5,3, max. 35W, white	LI111011
Optional Accessories	
LED lamp, QPAR111, GU10, 7W, 3000K 25° silver	LI1001570
MR16 SMD LED, 4W, 3000K, 225lm, 40°	LI551243
Transformer, 60VA, 12V, IP44	LI227160