

Datenblatt für Artikel: LI113986--

NEW TRIA MINI DL ROUND, 30°, 3000K, alu-brushed,

incl. MI-Plug & clip spring



Technische Daten

Cut-out size (mm)	Ø40
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	Aluminum brushed
Material	Aluminum
Manufacturer	O3-SLV
Emission angle (°)	30
Light source	LED
Watt (W)	2,20
System efficiency (lm/W)	65
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	143
Number of lamps	1
Live time	30.000h
Protection class	III

Technische Daten - Fortsetzung

IP Rating	IP44
Mounting depth (mm)	40
Illuminant incl.	yes
ØxH mm	52x36
Cut-out size mm	Ø40

Artikeltabelle

BEZEICHNUNG	BEST.NR.
NEW TRIA MINI DL ROUND, 30°, 3000K, alu-brushed, incl. MI-Plug & clip spring	LI113986
Optional Accessories	
Plugbar, 3 Exit with 2 Bridges, max. 700mA, black	LI111830
Plugbar, 6 Exit with 3 Bridges, max. 700mA, black	LI111831
cable extension for Article with 700mA, 1m	LI111832
LED-Driver 11W, 700mA, incl. strain relief	LI464030