

Datenblatt für Artikel: LI114216--

NEW TRIA 3 DL SQUARE Set, 3x6W, 3000K, 38°, alu brushed

incl. Driver & clip spring



Technische Daten

Net length (mm)	250,00
Net width (mm)	90,00
Net height (mm)	48,00
Net weight (kg)	0,80
Cut-out size (mm)	240x80
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	Aluminum brushed
Material	Aluminum
Manufacturer	03-SLV
Emission angle (°)	38
Operating voltage AC (V)	230
Light source	COB LED
Socket	GU10
Watt (W)	30
System efficiency (lm/W)	83
Light colour	warm white

Technische Daten - Fortsetzung

Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	2500
Number of lamps	3
Live time	40.000h
Protection class	I
Mounting depth (mm)	70
Illuminant incl.	yes
LxWxH mm	250x90x48
Cut-out size mm	240x80

Artikeltabelle

BEZEICHNUNG	BEST.NR.
NEW TRIA 3 DL SQUARE Set, 3x6W, 3000K, 38°, alu brushed incl. Driver & clip spring	LI114216