

Datenblatt für Artikel: LI146706--

# PIPOFLEX wall light, red-anodized, 4W, 3000K



## Technische Daten

|                             |                       |
|-----------------------------|-----------------------|
| Net length (mm)             | 230,00                |
| Net width (mm)              | 65,00                 |
| Net height (mm)             | 125,00                |
| Net weight (kg)             | 0,33                  |
| Mounting                    | surface mounting wall |
| Colour                      | Red                   |
| Material                    | Aluminum              |
| Manufacturer                | O3-SLV                |
| Emission angle (°)          | 35                    |
| Controller                  | LED driver            |
| Operating voltage AC (V)    | 230                   |
| Light source                | LED                   |
| Lamp holder                 | LED Platine           |
| Watt (W)                    | 4                     |
| System efficiency (lm/W)    | 50                    |
| Light colour                | warm white            |
| Colour temperature (K)      | 3000                  |
| Colour rendering index (Ra) | ≥80                   |

## Technische Daten - Fortsetzung

|                         |            |
|-------------------------|------------|
| Luminous flux (lm)      | 200        |
| Number of lamps         | 1          |
| Protection class        | I          |
| Energy efficiency class | A          |
| Illuminant incl.        | yes        |
| LxWxH mm                | 230x65x125 |

## Artikeltabelle

| BEZEICHNUNG                                  | BEST.NR. |
|----------------------------------------------|----------|
| PIPOFLEX wall light, red-anodized, 4W, 3000K | LI146706 |