

Datenblatt für Artikel: LI152062--

Downunder, RCL 101, square, brushed stainl.steel, LED, warmwhite



Technische Daten

Net length (mm)	47,00
Net width (mm)	125,00
Net height (mm)	65,00
Net weight (kg)	0,32
Cut-out size (mm)	114x54
Luminaire type	Recessed wall luminaire
Mounting	recessed wall mounting
Colour	Brushed Stainless steel
Material	Aluminum Stainless steel
Manufacturer	03-SLV
Controller	LED driver
Operating voltage AC (V)	24
Light source	SMD LED
Watt (W)	2
Light colour	warm white
Colour temperature (K)	3000

Technische Daten - Fortsetzung

Colour rendering index (Ra)	≥80
Luminous flux (lm)	190
Number of lamps	1
Protection class	III
Energy efficiency class	F
Mounting depth (mm)	45
Illuminant incl.	yes
LxWxH mm	47x125x65
Cut-out size mm	114x54

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Downunder, RCL 101, square, brushed stainl. steel, LED, warmwhite	LI152062
Optional Accessories	
LED power unit, 12W, 24V	LI470502
Unterputzrahmen für Downunder RCL 101	LI925201