


I-VIDUAL LED PANEL for ceiling grid 600x600, 4000K, white



Technische Daten

Net length (mm)	595,00
Net width (mm)	595,00
Net height (mm)	13,00
Net weight (kg)	3,92
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	White
Material	Acryl Aluminum
Manufacturer	03-SLV
Emission angle (°)	110
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	40
System efficiency (lm/W)	80
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80

Technische Daten - Fortsetzung

Luminous flux (lm)	3200
Number of lamps	2
Live time	30.000h
Protection class	III
Energy efficiency class	A++ A+ A
Mounting depth (mm)	50
Illuminant incl.	yes
LxWxH mm	595x595x13

Artikeltabelle

BEZEICHNUNG	BEST.NR.
I-VIDUAL LED PANEL for ceiling grid 600x600, 4000K, white	LI158704
Optional Accessories	
Universal-frame for LED-Panel, 595x595mm, white	LI158762
INSTALLATION FRAME, silver-grey, L/W 60.5/60.5 cm for I-VIDUAL LED panel	LI158764
rosette, 10,3cm x 22cm x 5,1cm, matt white	LI158791
Suspension set for LED Panel	LI158799
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032
LED-Driver, 40W, 1000mA, incl. strain relief	LI464170
LED-Driver, 40W, 1000mA, incl. strain relief, dimmable	LI464176