


Data Sheet for Article: LI158714--

I-VIDUAL LED PANEL for ceiling grid 625x625, 4000K, white



Technical Data

Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	White
Material	Acryl Aluminum
Manufacturer	O3-SLV
Emission angle (°)	110
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	40
System efficiency (lm/W)	80
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	3200
Number of lamps	2
Live time (h)	30000
Protection class	III

Technical Data - continued

Energy efficiency class	A++ A+ A
Mounting depth (mm)	50
Illuminant incl.	yes
LxWxH mm	617x617x13

Article Table

DESCRIPTION	Order No.
I-VIDUAL LED PANEL for ceiling grid 625x625, 4000K, white	LI158714
Optional Accessories	
Universal-frame for LED-Panel, 620x620mm, white	LI158772
INSTALLATION FRAME, silver-grey, L/W 62.5/62.5 cm for I-VIDUAL LED panel	LI158774
rosette, 10,3cm x 22cm x 5,1 cm, matt white	LI158791
Suspension set for LED Panel	LI158799
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032
LED-Driver, 40W, 1000mA, incl. strain relief	LI464170
LED-Driver, 40W, 1000mA, incl. strain relief, dimmable	LI464176