

Datenblatt für Artikel: LI158804--

# I-VIDUAL LED Panel for grid ceilings, 600x600mm, UGR<22, 4000K

white



## Technische Daten

|                      |                 |
|----------------------|-----------------|
| Net length (mm)      | 595,00          |
| Net width (mm)       | 595,00          |
| Net height (mm)      | 13,00           |
| Net weight (kg)      | 4,35            |
| Manufacturer         | 03-SLV          |
| Glare factor (UGR)   | <22             |
| Input voltage AC (V) | 1000mA   1050mA |
| Lamp holder          | LED Platine     |
| LxWxH mm             | 595x595x13      |

## Artikeltabelle

| BEZEICHNUNG                                                                      | BEST.NR. |
|----------------------------------------------------------------------------------|----------|
| I-VIDUAL LED Panel for grid ceilings, 600x600mm, UGR<22, 4000K<br>white          | LI158804 |
| <b>Optional Accessories</b>                                                      |          |
| Universal-frame for LED-Panel, 595x595mm, white                                  | LI158762 |
| INSTALLATION FRAME, silver-grey, L/W 60.5/60.5 cm<br>for I-VIDUAL LED panel      | LI158764 |
| rosette, 10,3cm x 22cm x 5,1cm, matt white                                       | LI158791 |
| Suspension set for LED Panel                                                     | LI158799 |
| TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable<br>inkl. Cable relief | LI464032 |
| LED-Driver, 40W, 1000mA, incl. strain relief                                     | LI464170 |
| LED-Driver, 40W, 1000mA, incl. strain relief, dimmable                           | LI464176 |