

Datenblatt für Artikel: LI162743--

SENDER LED recessed PANEL, 10W, 3000K, round, silvergrey



Technische Daten

Net height (mm)	30,00
Net diameter (mm)	180,00
Net weight (kg)	0,43
Cut-out size (mm)	Ø172
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	Silver grey
Material	Aluminum
Manufacturer	O3-SLV
Emission angle (°)	120
Controller	without LED Driver
Input current (A)	0,35
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	10
System efficiency (lm/W)	56
Light colour	warm white
Colour temperature (K)	3000

Technische Daten - Fortsetzung

Colour rendering index (Ra)	≥80
Luminous flux (lm)	560
Number of lamps	1
Live time	30.000h
Protection class	III
Energy efficiency class	A++ A+ A
Mounting depth (mm)	40
Illuminant incl.	yes
ØxH mm	180x30
Cut-out size mm	Ø172

Artikeltabelle

BEZEICHNUNG	BEST.NR.
SENDER LED recessed PANEL, 10W, 3000K, round, silvergrey	LI162743
Optional Accessories	
LED DRIVER 15W, dimmable, 350mA, incl. stress relief	LI464143