


Datenblatt für Artikel: LI162783--

SENDER LED recessed PANEL, 14W, 3000K, angular, white



Technische Daten

Net length (mm)	240,00
Net width (mm)	240,00
Net height (mm)	30,00
Net weight (kg)	0,86
Cut-out size (mm)	230x230
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	White
Material	Aluminum
Manufacturer	03-SLV
Emission angle (°)	120
Controller	without LED Driver
Input current (A)	0,35
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	14
System efficiency (lm/W)	69
Light colour	warm white

Technische Daten - Fortsetzung

Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	970
Number of lamps	1
Live time	30.000h
Protection class	III
Energy efficiency class	A++ A+ A
Mounting depth (mm)	40
Illuminant incl.	yes
LxWxH mm	240x240x30
Cut-out size mm	230x230

Artikeltabelle

BEZEICHNUNG	BEST.NR.
SENDER LED recessed PANEL, 14W, 3000K, angular, white	LI162783
Optional Accessories	
LED DRIVER 15W, dimmable, 350mA, incl. stress relief	LI464143
LED DRIVER 18W, dimmable, 350mA, incl. stress relief	LI464150