

Datenblatt für Artikel: LI230802--

NAUTILUS LED 304 B, 3x1W 3000K IP55, stainless steel brushed



Technische Daten

Net width (mm)	100,00
Net height (mm)	145,00
Net diameter (mm)	100,00
Net weight (kg)	0,86
Luminaire type	wall luminaires surface mounted floor luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall floor mounting
Colour	Brushed Stainless steel
Material	Stainless steel
Manufacturer	03-SLV
Emission angle (°)	45
Controller	LED driver
Operating voltage AC (V)	230
Light source	LED

Technische Daten - Fortsetzung

Lamp holder	LED Platine
Watt (W)	3x1
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	240
Number of lamps	1
Protection class	I
IP Rating	IP55
Energy efficiency class	A
Swivel range (°)	270
Illuminant incl.	yes
Diameter (mm)	100
ØxH mm	100x145

Artikeltabelle

BEZEICHNUNG	BEST.NR.
NAUTILUS LED 304 B, 3x1W 3000K IP55, stainless steel brushed	LI230802
Optional Accessories	
IP68 connection box, 3-pole	LI228730