

Datenblatt für Artikel: LI233550--

DASAR LED MINI 2W, 3000K, IP67, angular, Stainless steel

Recessed floor lamp, 12-24V, Driver have to be ordered separatly



Technische Daten

Net length (mm)	37,00
Net width (mm)	37,00
Net weight (kg)	0,35
Cut-out size (mm)	Ø30
Luminaire type	recessed floor luminaire
Mounting	in-ground mounted
Colour	Stainless steel
Material	Stainless steel Glass
Manufacturer	03-SLV
Emission angle (°)	31
Light source	LED
Lamp holder	LED Platine
Watt (W)	2
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80

Technische Daten - Fortsetzung

Luminous flux (lm)	120
Number of lamps	1
Live time	25.000h
Protection class	III
IP Rating	IP67
Energy efficiency class	A++ A+ A
Mounting depth (mm)	80
Illuminant incl.	yes
Cut-out size mm	Ø30

Artikeltabelle

BEZEICHNUNG	BEST.NR.
DASAR LED MINI 2W, 3000K, IP67, angular, Stainless steel	LI233550
Recessed floor lamp, 12-24V, Driver have to be ordered separatly	
Optional Accessories	
LED power unit, 12W, 24V	LI470502
LED power supply, 12W, 12V	LI470507