

Datenblatt für Artikel: LI29001242

Led Panel 33W 4000lm 840 1197x297mm 1050mA excl. Driver



Technische Daten

Netto lengte (mm)	1.197,00
Breedte (mm)	297,00
Hoogte (mm)	9,00
Nettogewicht (kg)	3,70
Omgevingstemperatuur min. (°C)	-20
Omgevingstemperatuur max. (°C)	40
Bevestiging	Plafondinbouw
Afwerking	Wit
Materiaal	Kunststof Metaal
Leverancier	Schrack
Stralingshoek (°)	80
Verblindingsfactor (UGR)	<19
Nominale werkspanning DC (V)	30-34
Bedrijfsstroom mA (mA)	1050
Lichtbron/ Lamp	SMD LED
Lampvoet	LED
Vermogen (W)	42

Technische Daten - Fortsetzung

Lichtrendement (lm/W)	105
Lichtkleur	Neutraalwit
Kleurtemperatuur (K)	4000
Kleurweergave-index (Ra)	≥85
Lichtstroom (lm)	4000
Levensduur	50.000h
Dimbaar	Ja
Beschermingsklasse	3
Beschermingsgraad	IP20
LxBxH mm	1197x297x9

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Led Panel 33W 4000lm 840 1197x297mm 1050mA excl. Driver	LI29001242
Optionele toebehoren	
Led Driver 47W, 100-240V CC 1050mA 30-42V DC	LI19001000
Led Driver 46W, 220-240V CC 1050mA 21-48V DC Dali	LI29001075
LED Driver 47W 220-240V CC 1050mA 4-48VDC 1-10V	LI29001076
Led Panel Surface Mounting Kit for 1197x297mm Serie Ledon	LI29001094
Led Panel Wall Bracket for Surface Mounting Kit Serie Ledon	LI29001097
Led Panel Suspension Kit 4x1M, Serie Ledon	LI29001064
Led Panel Suspension Kit 4x2M, Serie Ledon	LI29001096
Led Backlight 120 800lm, 110°, 840, 1050mA	LI29001142
Aftakdoos 3 weg IP20 veerklemmen	LID15379