

Datenblatt für Artikel: LI552425--

# FLEXLED ROLL SELECT 24V, 5m, 5000K



## Technische Daten

|                             |                                                                                         |
|-----------------------------|-----------------------------------------------------------------------------------------|
| Colour temperature (K)      | 5000                                                                                    |
| Light colour                | cool white                                                                              |
| Colour rendering index (Ra) | ≥80                                                                                     |
| Protection class            | III                                                                                     |
| Material                    | Plastic                                                                                 |
| Manufacturer                | O3-SLV                                                                                  |
| Light source                | LED                                                                                     |
| Luminaire type              | wall luminaires<br>surface mounted floor luminaire<br>surface mounted ceiling luminaire |

## Artikeltabelle

| BEZEICHNUNG                                                  | BEST.NR. |
|--------------------------------------------------------------|----------|
| FLEXLED ROLL SELECT 24V, 5m, 5000K                           | LI552425 |
| <b>Optional Accessories</b>                                  |          |
| LED power unit, 36W, 24V                                     | LI470544 |
| Feed in for Flexled Roll 12V up to 8mm width, length = 30cm  | LI550412 |
| Direct connector for Flexled Roll 12V up to 8mm width, 2 pcs | LI550415 |
| LED strip clip connector                                     | LI550560 |