


Datenblatt für Artikel: LID13238--

Sutil Round LED Panel 16W, 4000K, 1118lm, Ø237mm, grey **€ECONOMY**




Technische Daten

Cut-out size (mm)	Ø225
Luminaire type	LED Panel
Mounting	recessed wall mounting recessed mounting ceiling
Colour	Gray
Material	Aluminum
Cover	opal
Manufacturer	06-One Light
Emission angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Output voltage AC (V)	23-28
Output current (A)	0,5
Light source	SMD LED

Technische Daten - Fortsetzung

Watt (W)	16
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	1118
Number of lamps	1
Live time	30000
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Mounting depth (mm)	40
Illuminant incl.	yes
ØxH mm	240x14
Cut-out size mm	Ø225

Dimensioned drawing: Sutil Round LED Panel 16W, 4000K, 1118lm, Ø237mm, grey



Artikeltabelle

BEZEICHNUNG	BEST.NR.
Sutil Round LED Panel 16W, 4000K, 1118lm, Ø237mm, grey	LID13238