

Datenblatt für Artikel: LID13533--

Sutil Quadro LED Panel 16W, 3000K, 884lm, 168x168mm, grey **€ECONOMY**




Technische Daten

Cut-out size (mm)	152x152
Luminaire type	LED Panel
Mounting	recessed wall mounting recessed mounting ceiling
Colour	Gray
Material	Aluminum
Cover	opal
Manufacturer	06-One Light
Emission angle (°)	120
Controller	LED driver
Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Output voltage DC (V)	23-28
Output current (A)	0,50
Light source	SMD LED

Technische Daten - Fortsetzung

Watt (W)	16
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	884
Number of lamps	1
Live time	30000
Dimmable	yes with optional, dimmable driver
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Illuminant incl.	yes
LxWxH mm	168x168x20
Cut-out size mm	152x152

Dimensioned drawing: Sutil Quadro LED Panel 16W, 3000K, 884lm, 168x168mm, grey



Artikeltabelle

BEZEICHNUNG	BEST.NR.
Sutil Quadro LED Panel 16W, 3000K, 884lm, 168x168mm, grey	LID13533
Optional Accessories	
LED Driver 500mA 16W for Sutil and Plano, triac dimmable	LID13554