

Datenblatt für Artikel: LID14003--

Sutil Quadro2 LED 22W, 3000K, 1320lm, 120°, IP40, grey **ECONOMY**

LED recessed mounted panel




Technische Daten

Cut-out size (mm)	210x210
Luminaire type	LED Panel
Mounting	recessed mounting ceiling
Colour	Grey
Material	Aluminum
Manufacturer	06-One Light
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	230
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	22
Light colour	warm white
Colour temperature (K)	3000

Technische Daten - Fortsetzung

Colour rendering index (Ra)	≥80
Luminous flux (lm)	1320
Number of lamps	1
Dimmable	no
Protection class	II
IP Rating	IP40
Energy efficiency class	A
Mounting depth (mm)	50
Illuminant incl.	yes
LxWxH mm	225x225x22
Cut-out size mm	210x210

Dimensioned drawing: Sutil Quadro2 LED 22W, 3000K, 1320lm, 120°, IP40, grey



Artikeltabelle

BEZEICHNUNG	BEST.NR.
Sutil Quadro2 LED 22W, 3000K, 1320lm, 120°, IP40, grey	LID14003
LED recessed mounted panel	
Optional Accessories	
LED Driver 540mA 22W for Sutil 2, triac dimmable	LID14022