

Datenblatt für Artikel: LID15774--

Linear BU LED 40/20W 4000K 34°/120° 220-240V IP20 wit

Aluminium profiel verlichting 3800lm direct / 1800lm indirect



Produktinfo

40W UGR17 Linear system with with 48 LED spots and 20W uplight for suspended installation, ideal for offices. _x000D_ _x000D_ Complete with 1000mA + 500mA drivers_x000D_ _x000D_ Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtstroom (lm)	1800 3800
Lichtkleur	Koudwit
Kleurtemperatuur (K)	4000
Kleurweergave-index (Ra)	≥90
Verblindingsfactor (UGR)	<17
Regelen lichtintensiteit	Nee
Beschermingsklasse	I
Beschermingsgraad	IP20
Lichtmiddel inbegrepen	Inbegrepen
Lampvoet	LED
Stralingshoek (°)	34/120

Technische Daten - Fortsetzung

Vermogen (W)	90/95
Lichtrendement (lm/W)	95 / 90
Cos Phi	0,9
Vermogen (W)	40 20
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Bedrijfsstroom mA (mA)	500/1000
Frequentie (Hz)	50/60
Bevestiging	Pendelmontage
Pendellengte (mm)	300
Afwerking	Wit
Uitvoering	Aluminium
Lengte (mm)	1300
Breedte (mm)	70
Hoogte (mm)	35
Optionele toebehoren	LID15782--
LxBxH (mm)	1300x70x35

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Linear BU LED 40/20W 4000K 34°/120° 220-240V IP20 wit	LID 15774
Aluminium profiel verlichting 3800lm direct / 1800lm indirect	
Optionele toebehoren	
Hoekprofiel 90° voor linear profiel A, B, BU wit	LID 15782
Montage toebehoren	