

Datenblatt für Artikel: LID17285--

Kor-SQ 40W 3600-4000lm 3-5,7K CRI80 UGR19 IP20 230V wit

complete with 1000mA driver; 14 PLAFO



Produktinfo

60x60cm adjustable CCT surface mounted backlit LED panel with microprismatic diffuser. Uniform lighting, ideal for commercial applications. Complete with 1000mA driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtstroom (lm)	3600/4000/3800
Lichtkleur	Koudwit Warmwit Daglicht
Kleurtemperatuur (K)	3000;4000;5700
Kleurweergave-index (Ra)	≥80
Verblindingsfactor (UGR)	<19
Regelen lichtintensiteit	Neen
Beschermingsklasse	II
Beschermingsgraad	IP20
Lichtmiddel inbegrepen	Inbegrepen
Lampvoet	LED

Technische Daten - Fortsetzung

Lichtrendement (lm/W)	90
Vermogen (W)	40
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Ingangsspanning AC (V)	220-240
Bedrijfsstroom mA (mA)	1000
Frequentie (Hz)	50/60
Bevestiging	Plafondmontage
Afwerking	Wit
Uitvoering	Aluminium
	Staal
Lengte (mm)	600
Hoogte (mm)	42
Optionele toebehoren	LID 16949--

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Kor-SQ 40W 3600-4000lm 3-5,7K CRI80 UGR19 IP20 230V wit complete with 1000mA driver; 14 PLAFO	LID17285
Optionele toebehoren	
Schroefloze klem 32A 6-aansluitingen 26 ACCES&GADGETS	LID16949