

Datenblatt für Artikel: LID17286--

Kor-L 40W 3600-4000lm 3000-5700K CRI80 UGR19 IP20 230V wit

complete with 1000mA driver; 14 PLAFO



Produktinfo

30x120cm adjustable CCT surface mounted backlit LED panel with microprismatic diffuser. Uniform lighting, ideal for commercial applications. Complete with 1000mA driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtstroom (lm)	3600/4000/3800
Lichtkleur	Koudwit Warmwit Neutraalwit
Kleurtemperatuur (K)	4000 3000 5700
Kleurweergave-index (Ra)	≥80
Verblindingsfactor (UGR)	<19
Levensduur	50.000h
Regelen lichtintensiteit	Neen
Beschermingsklasse	II
Beschermingsgraad	IP20

Technische Daten - Fortsetzung

Lichtmiddel inbegrepen	Inbegrepen
Lampvoet	LED
Lichtrendement (lm/W)	90
Vermogen (W)	40
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Ingangsspanning AC (V)	220-240
Bedrijfsstroom mA (mA)	1000
Primaire stroom (A)	1
Frequentie (Hz)	50/60
Bevestiging	Plafondmontage
Kleur	Wit
Uitvoering	Aluminium Staal
Lengte (mm)	1200
Breedte (mm)	300
Hoogte (mm)	42
Optionele toebehoren	LID16949--
LxBxH (mm)	1200x300x42

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Kor-L 40W 3600-4000lm 3000-5700K CRI80 UGR19 IP20 230V wit complete with 1000mA driver; 14 PLAFO	LID17286
Optionele toebehoren	
Schroefloze klem 32A 6-aansluitingen 26 ACCES&GADGETS	LID16949