

Datenblatt für Artikel: LID17814--

Sai LED 20W 2000lm 3K/4K/5K CRI90 IP44 UGR19 230V 120° wit

13 WALL & CEIL LED



Produktinfo

CCT Variable 20W LED surface mounted downlight. IP44. Supplied with non-dimmable driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Hoogte (mm)	80,00
Netto diameter (mm)	130,00
Type verlichting	Aanbouw wandverlichting Plafondverlichting
Bevestiging	Wandbevestiging Plafondmontage
Kleur	Wit
Uitvoering	Aluminium
Stralingshoek (°)	90
Verblindingsfactor (UGR)	<19
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Ingangsspanning AC (V)	220-240

Technische Daten - Fortsetzung

Lampvoet	LED
Lichtrendement (lm/W)	100
Vermogen (W)	20
Lichtkleur	Koudwit Warmwit Neutraalwit
Kleurtemperatuur (K)	5000 4000 3000
Kleurweergave-index (Ra)	≥90
Lichtstroom (lm)	2000
Regelen lichtintensiteit	Nee
Beschermingsklasse	I
Beschermingsgraad	IP44
Diameter (mm)	68
ØxH (mm)	130x80

BEZEICHNUNG	BEST.NR.
Sai LED 20W 2000lm 3K/4K/5K CRI90 IP44 UGR19 230V 120° wit 13 WALL & CEIL LED	LID17814