

Datenblatt für Artikel: MAIM6200D-

LED steady light module, 230-240VAC, blue

Base required, Productgroep Constant licht, Bouwvorm Module, Bediening Constant,
Nominale spanning 230VAC- 240VACV




Technische Daten

Productgamma	MA 230V
Productgroep	Constant licht
LED-Kleur	Blauw
Nominale spanning (V)	230VAC- 240VAC
Bouwvorm	Module
Bediening	Constant
Beschermingsgraad	IP66
Diameter (mm)	70
Invoeringen	Afhankelijk van basis
Optionele toebehoren	MAIB0001--;MAIB0002--;MAIR0001--;MAIA3100--
Type lamp	LED
Lens	Polycarbonaat, Fresnel lens
Bevestiging	Vrije oriëntatie
Levensduur	100000
Temperatuursbereik - Werking (°C)	-30°C tot +60

Technische Daten - Fortsetzung

Slagvastheid	IK08
Nominale stroom (A)	0,03
Maximum aantal modules	5
Inbouwdiameter (mm)	70
Inschakelduur (% ED)	100
Lekstroom	3mA [bruikbaar PLC]

Dimension



Artikeltabelle

BEZEICHNUNG	BEST.NR.
LED steady light module, 230-240VAC, blue Base required, Productgroep Constant licht, Bouwvorm Module, Bediening Constant, Nominale spanning 230VAC- 240VACV	MAIM6200D
Optionele toebehoren	
Standard Base for Signal Towers modular, Black 1 to max. 5 modules per base mountable, including end cap, usable for all modules (230-240VAC and 24V AC/DC), Productgroep Toebehoren, Bouwvorm Lege sokkel, Type klemmen Veerklemmen	MAIB0001
Vertical Base for Signal Towers modular, Black 1 to max. 5 modules per base mountable, including end cap, usable for all modules (230-240VAC and 24V AC/DC), Productgroep Toebehoren, Bouwvorm Lege sokkel, Type klemmen Veerklemmen	MAIB0002
Tube base for Signal Towers, Alu-tube with plastic foot, 100mm 1 to max. 5 modules per base mountable, with plastic base 100mm, including end cap, usable for all modules (230-240VAC and 24V AC/DC), Productgroep Toebehoren, Bouwvorm Lege sokkel, Type klemmen Veerklemmen	MAIR0001
Multi-tone siren, 8 tones, 24V AC/DC Base required, only mountable as top modul, Productgroep Multi-toon, Bouwvorm Module, Bediening Dip schakelaars, Nominale spanning 24VAC/DCV	MAIA3100