

Datenblatt für Artikel: NLCC24-20-

Low power system CoreCompact24 24V AC 4/20

4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 250W
1h / 97W 3 h / 30W 8 h, optionally: Battery extension (NLBALI020), h x w x d: 455 x 250
x 230 mm



Technische Daten

Netto lengte (mm)	230,00
Breedte (mm)	250,00
Hoogte (mm)	455,00
Nettogewicht (kg)	13,00

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Low power system CoreCompact24 24V AC 4/20 4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 250W 1h / 97W 3 h / 30W 8 h, optionally: NLCC24-20 Battery extension (NLBALI020), h x w x d: 455 x 250 x 230 mm	
Optionele toebehoren	
E30 fire protection panel for LPS MI, CC with fan Outside dimensions: 918 x 711 x 345mm (HxWxD), colour RAL7035, 105kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30, for LPS MicroControl with 7Ah or 9Ah battery set and for LPS CoreCompact 24 with 40Ah battery set	NLMIE30A
Indicator panel with LED's For 24V AC LPS systems Core 24	NLCMA
Batterieexpansion CC24 LiFePO419.8Ah incl. connection cable for 2 batteries	NLBALI020